

CONTENTS

FOREWORD 7

1 Scope and object 11

2 Normative references 11

3 Definitions 13

 3.1 Components 13

 3.2 Operational characteristics 15

4 Classification 19

 4.1 Breaking range (see also Annex B) 19

 4.2 Utilisation category 19

5 Characteristics 19

6 Product information 21

 6.1 Documentation 21

 6.2 Marking 21

7 Normal service conditions 21

8 Constructional and performance requirements 23

 8.1 Constructional requirements 23

 8.2 Performance requirements 23

9 Tests 27

 9.1 Kinds of tests 27

 9.2 Tests for the verification of constructional requirements 29

 9.3 Type tests for the verification of performance requirements 29

 9.4 Routine tests for the verification of performance requirements 45

Annex A (normative) Connection diagram for temperature-rise tests 47

Annex B (informative) Comparison between “a” and “g” fuse time current characteristics 49

Annex C (informative) Diagram of the test circuit for breaking capacity tests 51

Annex D (informative) Verification of breaking capacity 53

Figure A.1 – Connection diagram for temperature-rise tests 47

Figure B.1 – Comparison between “a” and “g” fuse time current characteristics 49

Figure C.1 – Diagram of the test circuit for breaking capacity tests 51

Figure D.1 – Test circuit calibration 53

Figure D.2 – Breaking operation when the instant of arc initiation is after the peak value of the current 55

Figure D.3 – Breaking operation when the instant of arc initiation is prior to the peak value of the current 55

Table 1 – Conventional times for “g” fuse-links 21

Table 2 – Rated and test voltages for d.c. fuse-links supplied from the contact line 25

Table 3 – Sequence of tests for the highest rating of a homogenous series31

Table 4 – Sequence of tests for the lowest rating of a homogenous series33

Table 5 – Sequence of tests for intermediate ratings of a homogenous series35

Table 6 – Tolerances on test values35

Table 7 – Parameters for breaking capacity tests of d.c. fuse-links.....39

Table 8 – Time constant of the test circuit.....41