

Contents	Page
1 Scope	5
2 Preferred characteristics, ratings and severities for environmental and overload tests	5
2.1 Characteristics	5
2.1.1 Climatic severities	5
2.1.2 Temperature characteristics and temperature coefficients of resistance	6
2.1.3 Limits for change in resistance	7
2.2 Preferred value ratings	8
2.2.1 Rated resistance	8
2.2.2 Tolerances on rated resistance	8
2.2.3 Rated dissipation	8
2.2.4 Limiting element voltage	9
2.2.5 Insulation resistance	9
2.2.6 Insulation voltage	9
2.3 Severities for environmental and overload test	9
2.3.1 Drying	9
2.3.2 Vibration	10
2.3.3 Low air pressure	10
2.3.4 Bump	10
2.3.5 Shock	10
2.3.6 Overload	11
2.4 Information to be given in detail specification	11
2.4.1 Style	11
2.4.2 Rated dissipation	11
2.4.3 Limiting element voltage	11
2.4.4 Dimensions	12
2.4.5 Resistance range	12
2.4.6 Tolerances on rated resistance	12
2.4.7 Climatic category	12
2.4.8 Vibration severity	12
2.4.9 Low air pressure severity	12
2.4.10 Bump severity	13
2.4.11 Shock severity	13
2.4.12 Limits of resistance change after 1 000 h endurance test	13
2.4.13 Temperature characteristic of resistance	13
2.4.14 Overload	13
2.4.15 Derating curve	13
2.4.16 Marking	13
2.4.17 Ordering information	13
2.4.18 Additional information (not for inspection purposes)	13

3	Inspection	14
3.1	Formation of inspection lots	14
3.1.1	General	14
3.1.2	Lot-by-lot testing	14
3.1.3	Periodic testing	15
3.2	Test methods	15
3.3	Qualification approval	15
3.4	Assessed process average procedures (APA)	15
3.5	Delayed delivery	15
Tables		
Table 1	Percentage change in resistance	6
Table 2	Limits of change in resistance	7
Annexes		
A.1	Fixed sample size Qualification Approval test schedules for fixed power resistors	16
A.2	Fixed sample size Qualification Approval test schedule for fixed power resistors	21