

# TABLE OF CONTENTS

## CHAPTER 1 CRASH PULSE AND KINEMATICS

|                                                                                  |    |
|----------------------------------------------------------------------------------|----|
| 1.1 INTRODUCTION .....                                                           | 1  |
| 1.2 VEHICLE IMPACT MODES AND CRASH DATA RECORDING .....                          | 1  |
| 1.2.1 Accelerometer Mounting and Coordinate Systems .....                        | 3  |
| 1.3 DIGITAL FILTERING PRACTICE PER SAE J211 AND ISO 6487 .....                   | 4  |
| 1.3.1 Relationship Between Two Points in a Frequency Response Plot .....         | 8  |
| 1.3.2 Chebyshev and Butterworth Digital Filters .....                            | 9  |
| 1.3.3 Filter Type, Deceleration Magnitude, and Phase Delay .....                 | 11 |
| 1.3.4 Moving Window Averaging and Equivalent Cutoff Frequency .....              | 17 |
| 1.3.4.1 <i>Moving Window Averaging</i> .....                                     | 17 |
| 1.3.4.2 <i>Equivalent Cutoff Frequency</i> .....                                 | 19 |
| 1.4 BASIC KINEMATIC RELATIONSHIPS .....                                          | 21 |
| 1.4.1 Computing Acceleration from a Velocity-Displacement Curve .....            | 21 |
| 1.4.2 Particle Kinematics in a Gravitational Field .....                         | 24 |
| 1.4.2.1 <i>Car Jumping and Landing</i> .....                                     | 24 |
| 1.4.3 Slipping on an Incline – Down Push and Side Push .....                     | 29 |
| 1.4.4 Calculation of Safe Distance for Following Vehicle .....                   | 32 |
| 1.5 IMPACT AND EXCITATION: VEHICLE AND SLED TEST KINEMATICS .....                | 33 |
| 1.5.1 Vehicle Kinematics in a Fixed Barrier Impact .....                         | 33 |
| 1.5.2 Unbelted Occupant Kinematics .....                                         | 34 |
| 1.5.2.1 <i>Kinematics Based on Accelerometer Data</i> .....                      | 35 |
| 1.5.2.2 <i>Kinematics Based on Crash Film Records</i> .....                      | 37 |
| 1.5.2.3 <i>Vehicle Crush, Sled Displacement, and Crash Pulse Centroid</i> .....  | 37 |
| 1.6 VEHICLE AND OCCUPANT KINEMATICS IN FIXED OBJECT IMPACT .....                 | 38 |
| 1.6.1 Vehicle Kinematics in Different Test Modes .....                           | 38 |
| 1.6.2 Vehicle Energy Density .....                                               | 40 |
| 1.6.3 Occupant Kinematics in Different Test Modes .....                          | 41 |
| 1.7 KINEMATIC VARIABLES .....                                                    | 43 |
| 1.7.1 Use of Residual Energy Density in Air Bag Sensor Activation .....          | 44 |
| 1.7.2 Time Requirement for Air Bag Sensor Activation .....                       | 45 |
| 1.7.3 Vehicle-Occupant-Restraint (VOR) Interaction .....                         | 45 |
| 1.8 CASE STUDY: SINGLE VEHICLE-TREE IMPACT ACCIDENT .....                        | 48 |
| 1.8.1 Analysis of the Recorder Crash Data .....                                  | 49 |
| 1.8.2 Frequency Spectrum Analysis for Electronic Crash Sensing .....             | 52 |
| 1.8.3 Application of a Residual Energy Density Algorithm .....                   | 53 |
| 1.9 RESTRAINT COUPLING .....                                                     | 53 |
| 1.9.1 Restraint Specific Stiffness and Onset Rate of Occupant Deceleration ..... | 54 |
| 1.9.2 Occupant Response in the Restraint Coupling Phase .....                    | 55 |
| 1.9.3 Maximum Occupant Response, Timing, and Onset Rate .....                    | 59 |
| 1.9.4 Vehicle, Occupant, and Restraint (VOR) Analysis Charts .....               | 60 |
| 1.9.4.1 <i>3-D Contour Plots of the Occupant Response and Timing</i> .....       | 60 |
| 1.9.4.2 <i>Vehicle, Occupant, and Restraint (VOR) Analysis Charts</i> .....      | 62 |
| 1.9.5 VOR Trend Analysis Based on Car and Truck Test Results .....               | 66 |

|                                                                               |    |
|-------------------------------------------------------------------------------|----|
| 1.10 OCCUPANT RIDEDOWN ANALYSIS AND ENERGY MANAGEMENT .....                   | 67 |
| 1.10.1 Energy Density Model .....                                             | 71 |
| 1.10.1.1 <i>Equations of Motion and Energy Density of a Crash Model</i> ..... | 72 |
| 1.10.1.2 <i>Ridedown, Restraint Energy Densities, and Timings</i> .....       | 72 |
| 1.10.2 Validation of Energy Density Model in High Speed Crash .....           | 74 |
| 1.10.2.1 <i>Test Energy Densities</i> .....                                   | 74 |
| 1.10.2.2 <i>Model Energy Densities</i> .....                                  | 75 |
| 1.10.3 Contour Plots of Ridedown Efficiency and Occupant Response .....       | 78 |
| 1.10.4 Restraint Design with Constant Occupant Deceleration .....             | 80 |
| 1.10.5 Design Constraint and Trade-Off .....                                  | 82 |
| 1.11 REFERENCES .....                                                         | 83 |

## CHAPTER 2 CRASH PULSE CHARACTERIZATION

|                                                                            |     |
|----------------------------------------------------------------------------|-----|
| 2.1 INTRODUCTION .....                                                     | 85  |
| 2.2 MOMENT-AREA METHOD .....                                               | 85  |
| 2.2.1 Displacement Computation Without Integration .....                   | 86  |
| 2.2.2 Centroid Time and Characteristics Length .....                       | 87  |
| 2.2.3 Construction of Centroid Time and Residual Deformation .....         | 88  |
| 2.2.3.1 <i>Centroid of a Quarter-Sine Pulse</i> .....                      | 89  |
| 2.2.3.2 <i>Residual Deformation of a Quarter-Sine</i> .....                | 91  |
| 2.3 PULSE APPROXIMATIONS WITH NON-ZERO INITIAL DECELERATION .....          | 91  |
| 2.3.1 ASW (Average Square Wave) .....                                      | 91  |
| 2.3.2 ESW (Equivalent Square Wave) .....                                   | 92  |
| 2.3.2.1 <i>ESW Transient Analysis</i> .....                                | 93  |
| 2.3.3 Tipped Equivalent Square Wave (TESW) – Background .....              | 94  |
| 2.3.4 Derivation of TESW Parameters .....                                  | 95  |
| 2.3.4.1 <i>Deformation and Rebound Phase</i> .....                         | 96  |
| 2.3.5 Construction of TESW Parameters .....                                | 97  |
| 2.3.5.1 <i>Relationships Between TESW and ASW</i> .....                    | 98  |
| 2.3.6 Kinematic Comparisons of Test Pulse and Approximated Pulses .....    | 101 |
| 2.3.6.1 <i>Rear-Loaded</i> .....                                           | 101 |
| 2.3.6.2 <i>Front-Loaded</i> .....                                          | 104 |
| 2.4 PULSE APPROXIMATIONS WITH ZERO INITIAL DECELERATION .....              | 104 |
| 2.4.1 Fourier Equivalent Wave (FEW) .....                                  | 104 |
| 2.4.2 FEW Sensitivity Analysis with Boundary Conditions .....              | 105 |
| 2.4.3 Kinematics and Energy Comparison .....                               | 106 |
| 2.4.4 Use of FEW and Power Rate Density in Crash Severity Detection .....  | 109 |
| 2.4.4.1 <i>Discrimination of Pole Impact Crash Severity</i> .....          | 109 |
| 2.4.4.2 <i>Use of All Negative FEW Coefficients in Pole Tests</i> .....    | 112 |
| 2.4.5 Use of Pulse Curve Length in Crash Severity Detection .....          | 115 |
| 2.4.6 FEW Analysis on Body Mount Attenuation .....                         | 116 |
| 2.4.6.1 <i>Frame Impulse Attenuation by Body Mount</i> .....               | 117 |
| 2.4.7 FEW Analysis on Resonance .....                                      | 120 |
| 2.4.7.1 <i>Air Bag Sensor Bracket Design Analysis</i> .....                | 120 |
| 2.4.7.2 <i>Re-synthesis of a Crash Pulse Without Resonance</i> .....       | 122 |
| 2.4.8 Trapezoidal Wave Approximation (TWA) .....                           | 123 |
| 2.4.8.1 <i>Deriving the Closed-form Solutions for TWA Parameters</i> ..... | 123 |
| 2.4.9 Bi-slope Approximation (BSA) .....                                   | 125 |
| 2.4.9.1 <i>Comparison of Test Pulse, BSA, and TWA</i> .....                | 126 |

|                                                                   |                                                                   |     |
|-------------------------------------------------------------------|-------------------------------------------------------------------|-----|
| 2.4.10                                                            | Harmonic Pulses – Background                                      | 128 |
| 2.4.11                                                            | Halfsine Approximation                                            | 130 |
| 2.4.12                                                            | Haversine Approximation                                           | 133 |
| 2.4.13                                                            | Comparison of Halfsine and Haversine Pulses                       | 135 |
| 2.4.14                                                            | Response of Air Bag Sensor to Harmonic Pulses                     | 136 |
| 2.4.14.1                                                          | <i>Sensor Dynamic Equations</i>                                   | 138 |
| 2.4.14.2                                                          | <i>Gas-Damped Sensor Mathematical Relationship</i>                | 139 |
| 2.4.15                                                            | Head Injury Criteria                                              | 139 |
| 2.4.15.1                                                          | <i>HIC Topographs</i>                                             | 142 |
| 2.4.16                                                            | Application of HIC Formula in Head Interior Impact                | 144 |
| 2.5                                                               | REFERENCES                                                        | 145 |
| <br><b>CHAPTER 3 CRASH PULSE PREDICTION BY CONVOLUTION METHOD</b> |                                                                   |     |
| 3.1                                                               | INTRODUCTION                                                      | 147 |
| 3.2                                                               | TRANSFER FUNCTION VIA CONVOLUTION INTEGRAL                        | 148 |
| 3.2.1                                                             | Convolution Method and Applications                               | 149 |
| 3.2.2                                                             | Solution by the Least Square Error Method                         | 150 |
| 3.2.3                                                             | Matrix Properties and Snow-Ball Effect                            | 151 |
| 3.2.4                                                             | Case Studies: Computing Transfer Functions                        | 154 |
| 3.3                                                               | TRANSFER FUNCTION AND A SPRING-DAMPER MODEL                       | 157 |
| 3.3.1                                                             | FIR Coefficients and K-C Parameters of a Spring-Damper Model      | 158 |
| 3.3.2                                                             | Transfer Functions of Special Pulses                              | 160 |
| 3.4                                                               | BELTED AND UNBELTED OCCUPANT PERFORMANCE WITH AIR BAG             | 162 |
| 3.4.1                                                             | Test Vehicle and Occupant Responses                               | 163 |
| 3.4.2                                                             | Truck #1: Unbelted Occupant with Full-Powered Air Bag             | 166 |
| 3.4.2.1                                                           | <i>Restraint FIR Model Validation Using Test Results</i>          | 167 |
| 3.4.2.2                                                           | <i>Filtered Signals of FIR Coefficients</i>                       | 167 |
| 3.4.2.3                                                           | <i>Response Prediction using TWA</i>                              | 168 |
| 3.4.3                                                             | Truck #2: Belted Occupant with Depowered Air Bag                  | 168 |
| 3.4.3.1                                                           | <i>Restraint Transfer Function Validation</i>                     | 168 |
| 3.4.3.2                                                           | <i>Response Prediction Using TWA</i>                              | 169 |
| 3.4.3.3                                                           | <i>Response Prediction Using Fourier Equivalent Wave (FEW)</i>    | 169 |
| 3.5                                                               | BODY MOUNT AND TORSO RESTRAINT TRANSFER FUNCTIONS                 | 170 |
| 3.5.1                                                             | Body Mount Characteristics and Transient Transmissibility         | 171 |
| 3.5.2                                                             | Types F and T Body Mount Transfer Functions                       | 173 |
| 3.5.3                                                             | Body Response Prediction of Truck T with Type F Body Mount        | 174 |
| 3.5.3.1                                                           | <i>Frame Impulse Duration and Transient Transmissibility</i>      | 174 |
| 3.5.3.2                                                           | <i>Testing Frame Rail for a Desired Impulse Duration</i>          | 175 |
| 3.5.4                                                             | Torso Restraint Transfer Functions                                | 176 |
| 3.5.4.1                                                           | <i>Vehicle and Belted Occupant Performances in Trucks F and T</i> | 176 |
| 3.5.4.2                                                           | <i>Truck T Response Prediction with Truck F Restraints</i>        | 179 |
| 3.6                                                               | EFFECT OF SLED AND BARRIER PULSES ON OCCUPANT RESPONSE            | 181 |
| 3.7                                                               | OTHER APPLICATIONS                                                | 183 |
| 3.8                                                               | RESPONSE INVERSE FILTERING (RIF)                                  | 184 |
| 3.8.1                                                             | Forward Prediction by Finite Impulse Response (FIR)               | 184 |
| 3.8.2                                                             | Inverse Filtering (IF)                                            | 186 |
| 3.8.3                                                             | Crash Pulse Prediction using FIR and RIF                          | 187 |
| 3.8.3.1                                                           | <i>Transferring [X] to [Y] with [H].</i>                          | 187 |
| 3.8.3.2                                                           | <i>Transfer [Y] to [X] with [H]'</i>                              | 188 |

|                                                       |     |
|-------------------------------------------------------|-----|
| 3.8.3.3 Transferring [Y] to [X] using [IF] .....      | 189 |
| 3.8.4 RIF Application in Frame Pulse Prediction ..... | 190 |
| 3.9 REFERENCES .....                                  | 192 |

**CHAPTER 4 BASICS OF IMPACT AND EXCITATION MODELING**

|                                                                             |     |
|-----------------------------------------------------------------------------|-----|
| 4.1 INTRODUCTION .....                                                      | 193 |
| 4.2 IMPACT AND EXCITATION – RIGID BARRIER AND HYGIE SLED TESTS .....        | 193 |
| 4.2.1 Vehicle and Sled/Unbelted Occupant Impact Kinematics .....            | 197 |
| 4.2.1.1 A Vehicle-to-Barrier Displacement Model .....                       | 197 |
| 4.2.1.2 Unbelted Occupant Kinematics .....                                  | 199 |
| 4.3 RIDEDOWN EXISTENCE CRITERIA AND EFFICIENCY .....                        | 201 |
| 4.3.1 Vehicle and Occupant Transient Kinematics .....                       | 201 |
| 4.3.1.1 EOM for Vehicle .....                                               | 202 |
| 4.3.1.2 EOM for Occupant .....                                              | 202 |
| 4.3.2 Derivation of Ridedown Existence Criteria .....                       | 202 |
| 4.3.2.1 Method I .....                                                      | 202 |
| 4.3.2.2 Method II .....                                                     | 203 |
| 4.3.3 Application of Ridedown Existence Criteria .....                      | 204 |
| 4.3.3.1 Case Study – High Speed Crash .....                                 | 204 |
| 4.3.3.2 Case Study – Low Speed Crash .....                                  | 205 |
| 4.3.4 Occupant Response Surface and Sensitivity .....                       | 205 |
| 4.3.4.1 Restraint Design Optimization by Response Contour Plots .....       | 206 |
| 4.3.4.2 Sensitivity of Occupant Response to ESW .....                       | 207 |
| 4.3.4.3 Sensitivity of Occupant Response to Dynamic Crush .....             | 208 |
| 4.3.4.4 Statistical Regression of Test Data and Model Responses .....       | 209 |
| 4.3.4.5 Response Prediction and Ridedown Efficiency .....                   | 210 |
| 4.4 BASICS OF SPRING AND DAMPER DYNAMIC MODELING .....                      | 212 |
| 4.4.1 Spring and Damper Elements .....                                      | 213 |
| 4.4.2 Properties of Viscoelastic Materials and Damping .....                | 214 |
| 4.4.2.1 Equivalent Viscous Damping .....                                    | 214 |
| 4.4.3 2-Mass (Vehicle-to-Vehicle) Impact Model .....                        | 214 |
| 4.4.4 Dynamic Equivalency Between Two-Mass and Effective Mass Systems ..... | 215 |
| 4.5 VEHICLE TO BARRIER (VTB) IMPACT: SPRING-MASS MODEL .....                | 216 |
| 4.5.1 Model Formulation .....                                               | 216 |
| 4.5.2 Design and Trend Analysis .....                                       | 218 |
| 4.5.2.1 Acceleration Function .....                                         | 218 |
| 4.5.2.2 Dynamic Crush Function .....                                        | 218 |
| 4.5.2.3 Estimating Time of Dynamic Crush, $T_m$ .....                       | 219 |
| 4.5.2.4 Response Properties as a Function of V and C .....                  | 220 |
| 4.5.2.5 Mass and Stiffness Ratios in Vehicle-to-Vehicle Impact .....        | 220 |
| 4.5.3 Effect of Test Weight Change on Dynamic Responses .....               | 221 |
| 4.6 SPRING-MASS OCCUPANT MODEL SUBJECTED TO EXCITATION .....                | 225 |
| 4.6.1 Response Solutions due to TESW and Sinusoidal Excitation .....        | 226 |
| 4.6.1.1 Model with TESW Excitation, $(E + j t)$ .....                       | 227 |
| 4.6.1.2 Sine Excitation $(E \sin \omega t)$ .....                           | 229 |
| 4.6.2 Model Response due to Sinusoidal Displacement Excitation .....        | 232 |
| 4.7 VEHICLE-TO-VEHICLE (VTV) IMPACT: SPRING-MASS MODEL .....                | 235 |
| 4.7.1 Crash Pulse Approximation by TESW and Sinusoidal Waves .....          | 235 |
| 4.7.1.1 Relative Motion Analysis (An Effective Mass System) .....           | 235 |

|                                                                          |     |
|--------------------------------------------------------------------------|-----|
| 4.7.1.2 Individual Vehicle Response Analysis                             | 237 |
| 4.7.2 Comparison of Sinusoidal Wave with Test Crash Pulse                | 238 |
| 4.7.3 Truck and Car Occupant Responses due to Halfsine Excitation        | 238 |
| 4.7.4 Elasto-plastic Modeling                                            | 240 |
| 4.8 A MAXWELL MODEL                                                      | 242 |
| 4.8.1 A Damper-Mass System (without Oscillatory Motion)                  | 243 |
| 4.8.2 The Maxwell Spring-Damper Model                                    | 244 |
| 4.8.3 Alternate Method: Zero Mass Between Maxwell Spring and Damper      | 244 |
| 4.8.4 Transition and Infinite Damping Coefficients                       | 246 |
| 4.8.4.1 Transition Damping Coefficient, $c^*$                            | 246 |
| 4.8.4.2 Infinite Damping Coefficient, $c=\infty$                         | 246 |
| 4.8.5 Model Response Characteristics with Transition Damping Coefficient | 247 |
| 4.9 IMPACT ON KELVIN MODEL-VEHICLE OR COMPONENT                          | 251 |
| 4.9.1 Transient and Major Responses of Kelvin Model                      | 251 |
| 4.9.1.1 Underdamped System ( $\zeta < 1$ )                               | 252 |
| 4.9.1.2 Critically Damped System ( $\zeta = 1$ )                         | 254 |
| 4.9.1.3 Overdamped System ( $\zeta > 1$ )                                | 255 |
| 4.9.1.4 Normalized Response Comparisons of Three Damping Systems         | 256 |
| 4.9.2 Factors Affecting the Pulse Shape of System with Various Damping   | 257 |
| 4.9.3 Hysteresis Loop                                                    | 260 |
| 4.9.4 Coefficient of Restitution and Damping Factor ( $\zeta$ )          | 263 |
| 4.9.5 Contact Duration                                                   | 264 |
| 4.10 DAMPING FACTOR AND NATURAL FREQUENCY FROM TESTS                     | 265 |
| 4.10.1 Conversions of the Stiffness and Damping Coefficient              | 267 |
| 4.10.2 Application to SUV and Sedan Frontal Structure Properties         | 267 |
| 4.11 EXCITATION OF THE KELVIN MODEL — OCCUPANT AND RESTRAINT             | 269 |
| 4.11.1 General Crash Pulse Excitation by Fourier Series                  | 272 |
| 4.11.1.1 Testing the Haversine Excitation                                | 272 |
| 4.11.2 Effect of Restraint Damping Control on Occupant Response          | 273 |
| 4.12 REFERENCES                                                          | 274 |

## CHAPTER 5 RESPONSE PREDICTION BY NUMERICAL METHODS

|                                                                      |     |
|----------------------------------------------------------------------|-----|
| 5.1 INTRODUCTION                                                     | 275 |
| 5.2 HYBRID MODEL — A STANDARD SOLID MODEL                            | 275 |
| 5.2.1 E.O.M. for Hybrid Model                                        | 276 |
| 5.2.2 Dynamic Response and Principles of Superposition               | 277 |
| 5.2.3 Combination of Two Hybrid Models                               | 278 |
| 5.2.4 Dynamic Equivalency between Two Non-Isomorphic Hybrid Models   | 280 |
| 5.2.4.1 Dynamic Equivalency in Transient Kinematics and Crush Energy | 282 |
| 5.3 TWO MASS-SPRING-DAMPER MODEL                                     | 283 |
| 5.3.1 Solutions of the Characteristic Equation                       | 284 |
| 5.3.2 Vehicle Displacement Responses in Fixed Barrier Impact         | 287 |
| 5.3.3 Application in Pre-Program Vehicle Structural Analysis         | 289 |
| 5.3.4 Application in Post-Crash Structural Analysis                  | 291 |
| 5.4 NATURAL FREQUENCIES IN TWO-MASS SYSTEM                           | 292 |
| 5.4.1 Formulas for the Natural Frequencies                           | 293 |
| 5.4.1.1 Decoupling of a Two-Mass System                              | 294 |
| 5.4.2 Natural Frequency Ratio and Stiffness Computation              | 294 |
| 5.4.3 Add-On or Splitting of a Spring-Mass Model                     | 295 |

|         |                                                                                                       |     |
|---------|-------------------------------------------------------------------------------------------------------|-----|
| 5.4.3.1 | <i>Doubled-Up of a Spring-Mass Model</i>                                                              | 295 |
| 5.4.3.2 | <i>Splitting of a Spring-Mass Model</i>                                                               | 296 |
| 5.5     | NUMERICAL SEARCHING TECHNIQUES                                                                        | 298 |
| 5.5.1   | Imbedded Random Search (IRS)                                                                          | 298 |
| 5.5.2   | Newton-Raphson Search Algorithm                                                                       | 300 |
| 5.6     | LOADING AND UNLOADING SIMULATION                                                                      | 301 |
| 5.6.1   | Loading Phase Simulation                                                                              | 301 |
| 5.6.2   | Unloading Phase Simulation                                                                            | 302 |
| 5.6.3   | Model with Power Curve Loading and Unloading                                                          | 303 |
| 5.6.3.1 | <i>Unloading Parameters <math>k'</math>, <math>n'</math>, and <math>x_i</math> in Reloading Cycle</i> | 304 |
| 5.6.3.2 | <i>Deceleration Contributions of Spring and Damper</i>                                                | 306 |
| 5.7     | A LUMPED-PARAMETER MODEL — CRUSH II                                                                   | 307 |
| 5.7.1   | Simple Structure Force-Deflection Table                                                               | 307 |
| 5.7.2   | Push Bumper Force-Deflection Data                                                                     | 308 |
| 5.7.3   | Basic Operation of EA Types                                                                           | 312 |
| 5.7.4   | Basic Operation of CV Factor (Velocity Sensitive Factor)                                              | 314 |
| 5.7.5   | Coefficient of Restitution, Static, and Dynamic Crush Relationship                                    | 314 |
| 5.7.5.1 | <i>1-mass Model with Elasto-Plastic Spring</i>                                                        | 315 |
| 5.8     | SIDE-IMPACT AND FRONTAL OFFSET MODELS                                                                 | 317 |
| 5.8.1   | Side Impact Model                                                                                     | 318 |
| 5.8.2   | Frontal Offset Impact                                                                                 | 320 |
| 5.8.2.1 | <i>Basic Concepts in Offset Impact Modeling</i>                                                       | 320 |
| 5.8.2.2 | <i>Full Barrier and Frontal Offset Test Results</i>                                                   | 321 |
| 5.8.2.3 | <i>Modeling the Full Barrier and Frontal Offset Tests</i>                                             | 323 |
| 5.8.2.4 | <i>Optimal Vehicle Structure for Both Full Frontal and Offset Tests</i>                               | 323 |
| 5.8.2.4 | <i>An Offset Lumped-Mass Model</i>                                                                    | 324 |
| 5.9     | REFERENCES                                                                                            | 325 |

## CHAPTER 6 IMPULSE, MOMENTUM, AND ENERGY

|       |                                                                   |     |
|-------|-------------------------------------------------------------------|-----|
| 6.1   | INTRODUCTION                                                      | 327 |
| 6.2   | BACKGROUND                                                        | 327 |
| 6.2.1 | Impulse and Momentum for a Single Particle                        | 328 |
| 6.2.2 | Impulse and Momentum for a System of Particles                    | 330 |
| 6.3   | CENTER OF GRAVITY AND MOTION THEOREM                              | 330 |
| 6.3.1 | Location and Motion of Center of Mass                             | 331 |
| 6.3.2 | Conservation of Momentum and CG Formula                           | 332 |
| 6.3.3 | CG Motion Theorem                                                 | 333 |
| 6.3.4 | Use of CG Motion Theorem in a Three-Car Collision Analysis        | 336 |
| 6.4   | IMPULSE AND CIRCLE OF CONSTANT ACCELERATION                       | 341 |
| 6.4.1 | Derivation of Acceleration at Point Q                             | 342 |
| 6.4.2 | Circle of Constant Acceleration (COCA)                            | 344 |
| 6.4.3 | Construction of COCA Given the Acceleration Ratio, $c$            | 345 |
| 6.4.4 | COCA Case Studies                                                 | 346 |
| 6.4.5 | Determination of the Direction of Acceleration, $a_Q$             | 349 |
| 6.4.6 | COCA Evaluation of Impact Severity                                | 349 |
| 6.4.7 | Given the Coordinates of Point Q, Find the Acceleration Ratio $c$ | 351 |
| 6.4.8 | Distributed Loading by Superposition                              | 352 |
| 6.5   | PRINCIPLE OF WORK AND ENERGY                                      | 353 |
| 6.5.1 | Applications using Principle of Impulse, Momentum, and Energy     | 354 |

|                                                                           |     |
|---------------------------------------------------------------------------|-----|
| 6.5.2 Drop Test and Impact Using a Spring Having Finite Weight .....      | 356 |
| 6.5.2.1 Drop Test on a Weightless Spring .....                            | 356 |
| 6.5.2.2 Drop Test Using a Spring Having Finite Weight .....               | 357 |
| 6.5.2.3 Horizontal Impact on a Bar/Spring .....                           | 359 |
| 6.5.2.4 Vertical Impact on a Beam/Spring .....                            | 360 |
| 6.5.3 Rebound Criterion in a Two-Mass Impact .....                        | 360 |
| 6.5.4 Separation Kinematics in a Multi-Mass Impact .....                  | 362 |
| 6.5.4.1 Separation Kinematics in a 3-Vehicle Collision .....              | 363 |
| 6.5.5 COR, Times of Dynamic Crush, and Separation Time .....              | 364 |
| 6.5.6 Coefficient of Restitution and Stiffness in Vehicle Crashes .....   | 365 |
| 6.6 VEHICLE INERTIA PROPERTIES AND CRITICAL SLIDING VELOCITY .....        | 368 |
| 6.6.1 CG Height Determination .....                                       | 368 |
| 6.6.2 Moment of Inertia Using Trifilar Pendulum Method .....              | 370 |
| 6.6.3 Moment of Inertia Using Swinging Pendulum Method .....              | 373 |
| 6.6.4 Critical Sliding Velocity (CSV) .....                               | 374 |
| 6.6.4.1 Derivation of CSV Formulas .....                                  | 374 |
| 6.6.4.2 Normalized CSV Equation and Applications .....                    | 376 |
| 6.7 ROLLOVER CRASHES .....                                                | 379 |
| 6.7.1 Rollover Dynamics of a Rigid Vehicle in a Steady Turn .....         | 379 |
| 6.7.2 Rollover Detection and Threshold Criterion of a Rigid Vehicle ..... | 381 |
| 6.7.3 Transient Rollover Dynamics of a Rigid Vehicle .....                | 382 |
| 6.7.3.1 Transient Rollover Without Lateral Acceleration .....             | 383 |
| 6.7.3.2 Transient Rollover With Lateral Acceleration .....                | 384 |
| 6.7.4 Rollover and Yaw Detections .....                                   | 386 |
| 6.8 ECCENTRIC LOADING ON VEHICLE ROLLOVER .....                           | 386 |
| 6.8.1 Vector Method for Eccentric Loading Analysis .....                  | 386 |
| 6.8.2 Rollover Kinematics Using the Vector Method .....                   | 388 |
| 6.8.3 Conditions for a Vehicle to Stop Rolling Following Rollover .....   | 390 |
| 6.9 REFERENCES .....                                                      | 394 |

**CHAPTER 7 CRASH SEVERITY AND RECONSTRUCTION**

|                                                                             |     |
|-----------------------------------------------------------------------------|-----|
| 7.1 INTRODUCTION .....                                                      | 395 |
| 7.2 OCCUPANT MOTION UNDER IMPACT AND EXCITATION .....                       | 395 |
| 7.2.1 Two-Degree-of-Freedom Occupant Model .....                            | 395 |
| 7.2.2 Effect of Seat Belt and Pretensioner on Occupant Kinematics .....     | 398 |
| 7.3 PRELOADING ON AN OCCUPANT .....                                         | 399 |
| 7.3.1 Modeling Pretensioning Effects in a System Test .....                 | 399 |
| 7.3.2 Modeling Pretensioning Effects in a Component Test .....              | 403 |
| 7.3.3 Transient Analysis of a Preloaded Model — Impact and Excitation ..... | 405 |
| 7.4 CENTRAL COLLISIONS .....                                                | 407 |
| 7.4.1 A Collision Experiment .....                                          | 408 |
| 7.4.2 Relative Motion During Impact .....                                   | 410 |
| 7.4.3 Kelvin’s Theorem, Total Crush, and Dissipated Energies .....          | 412 |
| 7.4.4 Total Crush Energy .....                                              | 413 |
| 7.4.5 Individual Crush Energy .....                                         | 415 |
| 7.5 NON-CENTRAL COLLISIONS .....                                            | 416 |
| 7.5.1 Case Study 1: Central Collision .....                                 | 419 |
| 7.5.2 Case Study 2: Non-central or Offset Collision .....                   | 420 |
| 7.6 USE OF ΔV AND BEV IN CRASH SEVERITY ASSESSMENT .....                    | 420 |

7.6.1 Crash Severity Index ..... 422

7.6.1.1 Compatibility by Equal Crash Severity Index ..... 423

7.6.2 Crash Momentum Index ..... 424

7.6.3 Crash Severity Assessment by a Power Curve Model ..... 425

7.6.3.1 *Power Curve Model and Methodology* ..... 425

7.6.3.2 *Power Curve Force-Deflections* ..... 425

7.6.3.3 *Computation of Barrier Equivalent Velocity (BEV)* ..... 427

7.7 VEHICLE ACCELERATION AND CRASH SEVERITY ..... 429

7.7.1 Damage Boundary Curve ..... 429

7.7.1.1 *Construction Steps for DBC* ..... 430

7.7.1.2 *Mechanic Principles of DBC* ..... 431

7.7.2 Crash Severity Assessment in Vehicle-to-Vehicle Compatibility Test ..... 432

7.7.2.1 *Vehicle Crush Characteristics* ..... 432

7.7.2.2 *Vehicle Peak Responses* ..... 434

7.8 VELOCITY AND ENERGY DISTRIBUTIONS IN TWO-VEHICLE IMPACT ..... 435

7.8.1 Kelvin’s Theorem ..... 435

7.8.1 Lumped Mass Modeling on Crash Severity ..... 441

7.9 INTERMEDIATE MASS EFFECT ..... 443

7.10 MODELING THE VEHICLE-TO-VEHICLE COMPATIBILITY TEST ..... 446

7.10.1 Models with Same Effective Stiffness ..... 446

7.10.2 Models with Different Effective Stiffness ..... 450

7.11 ACCIDENT RECONSTRUCTION METHODOLOGY ..... 452

7.11.1 Background ..... 452

7.11.2 Vehicle Size and Stiffness Coefficient Categories ..... 455

7.11.2.1 *Computing Stiffness Coefficients, Intercept and Slope* ..... 456

7.11.3 Stiffness Coefficient Comparison Between Data Base and Crash Tests ..... 457

7.11.4 Four-Way Plot of Stiffness Coefficients and Responses ..... 457

7.11.5 Non-Linear Crush Profile and Force Deflection Data ..... 459

7.11.5.1 *Non-Linear Crush Profile* ..... 459

7.11.5.2 *Elasto-Plastic Force Deflection* ..... 459

7.11.5 Estimate of the Impact Severity and Sensor Performance in a Van Impact ..... 460

7.11.5.1 *Estimate of the Vehicle Impact Severity* ..... 460

7.11.5.2 *Estimate of the Sensor Performance* ..... 461

7.12 REFERENCES ..... 462

**LIST OF FIGURES ..... 463**

**UNIT CONVERSIONS ..... 475**

**INDEX ..... 477**