

CONTENTS

FOREWORD	5
1 Scope	7
2 Normative references	7
3 Terms and definitions	8
4 General test conditions	9
5 Test methods and requirements	10
5.1 General	10
5.1.1 Overview	10
5.1.2 Exceptions	10
5.2 Immunity	10
5.2.1 General	10
5.2.2 Function performance criteria	11
5.2.3 Test severity level	11
5.2.4 Immunity of vehicles to electrical fast transient/burst disturbances conducted along AC and DC power lines	12
5.2.5 Immunity of vehicles to surges conducted along AC and DC power lines	12
5.2.6 Immunity to electromagnetic radiated RF-fields	15
5.2.7 Immunity to pulses on supply lines	20
5.2.8 Immunity test and severity level overview	20
5.3 Emissions	23
5.3.1 Test conditions	23
5.3.2 Emissions of harmonics on AC power lines	23
5.3.3 Emission of voltage changes, voltage fluctuations and flicker on AC power lines	26
5.3.4 High-frequency conducted disturbances on AC or DC power lines	27
5.3.5 High-frequency conducted disturbances on network and telecommunication access	30
5.3.6 High-frequency radiated disturbances	32
5.3.7 Radiated disturbances on supply lines	37
Annex A (normative) Artificial networks, asymmetric artificial networks and integration of charging stations into the test setup	38
A.1 Overview	38
A.2 Charging station and power mains connection	38
A.3 Artificial networks (AN)	39
A.3.1 General	39
A.3.2 Low voltage (LV) powered component	39
A.3.3 High voltage (HV) powered component	40
A.3.4 Components involved in charging mode connected to DC power supply	42
A.4 Artificial mains networks (AMN)	43
A.5 Asymmetric artificial networks (AAN)	43
A.5.1 General	43
A.5.2 Symmetric communication lines (e.g. CAN)	43
A.5.3 PLC on power lines	44
A.5.4 PLC (technology) on control pilot	45
Bibliography	47
Figure 1 – Electrical fast transient/burst test vehicle setup	12

Figure 2 – Vehicle in configuration "REESS charging mode coupled to the power grid" – coupling between lines for AC (single phase) and DC power lines.....	13
Figure 3 – Vehicle in configuration "REESS charging mode coupled to the power grid" – coupling between each line and earth for AC (single phase) and DC power lines	13
Figure 4 – Vehicle in configuration "REESS charging mode coupled to the power grid" – coupling between lines for AC (three phases) power lines.....	14
Figure 5 – Vehicle in configuration "REESS charging mode coupled to the power grid" – coupling between each line and earth for AC (three phases) power lines	14
Figure 6 – Example of test setup for vehicle with inlet located on the vehicle side (AC/DC power charging without communication).....	16
Figure 7 – Example of test setup for vehicle with inlet located at the front/rear of the vehicle (AC/DC power charging without communication)	17
Figure 8 – Example of test setup for vehicle with inlet located on vehicle side (AC or DC power charging with communication).....	18
Figure 9 – Example of test setup for vehicle with inlet located at the front/rear of the vehicle (AC or DC power charging with communication).....	19
Figure 10 – Vehicle in configuration "REESS charging mode coupled to the power grid" – Single-phase charger test setup.....	25
Figure 11 – Vehicle in configuration "REESS charging mode coupled to the power grid" – Three-phase charger test setup	25
Figure 12 – Vehicle in configuration "REESS charging mode coupled to the power grid"	26
Figure 13 – Vehicle in configuration "REESS charging mode coupled to the power grid"	29
Figure 14 – Vehicle in configuration "REESS charging mode coupled to the power grid"	31
Figure 15 – Example of vehicle in configuration "REESS charging mode coupled to the power grid"	34
Figure 16 – Test configuration for ESAs involved in REESS charging mode coupled to the power grid (example for horn antenna).....	36
Figure A.1 – Example of 5 μ H AN schematic	39
Figure A.2 – Characteristics of the AN impedance	40
Figure A.3 – Example of 5 μ H HV AN schematic	41
Figure A.4 – Characteristics of the HV AN impedance.....	41
Figure A.5 – Example of 5 μ H HV AN combination in a single shielded box.....	42
Figure A.6 – Impedance matching network attached between HV ANs and EUT	42
Figure A.7 – Example of an impedance stabilization network for symmetric communication lines	44
Figure A.8 – Example of a circuit for emission tests of PLC on AC or DC powerlines	45
Figure A.9 – Example of a circuit for immunity tests of PLC on AC or DC powerlines	45
Figure A.10 – Example of a circuit for emission tests of PLC on control pilot line	46
Figure A.11 – Example of a circuit for immunity tests of PLC on control pilot line	46
Table 1 – Immunity tests	21
Table 2 – Maximum allowed harmonics (input current ≤ 16 A per phase)	24
Table 3 – Acceptable harmonics for $R_{Sce} = 33$ ($16 \text{ A} < I_i \leq 75 \text{ A}$).....	24
Table 4 – Maximum allowed radiofrequency conducted disturbances on AC power lines	27
Table 5 – Maximum allowed radiofrequency conducted disturbances on DC power lines.....	28
Table 6 – Maximum allowed radiofrequency conducted disturbances on network and telecommunication access	30

Table 7 – Maximum allowed vehicle high-frequency radiated disturbances32

Table 8 – Maximum allowed ESA high-frequency radiated disturbances35

Table 9 – Maximum allowed ESA radiated disturbances on supply lines37