

Contents

	Page
Foreword	v
Introduction	vi
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 THCD selection and THCD types	3
4.1 Selection	3
4.2 Types of THCD	4
5 Requirements for the design of two-hand control devices	4
5.1 General	4
5.2 Use of both hands (simultaneous actuation)	4
5.3 Relationship between actuation by hand and output signal(s)	4
5.4 Cessation of the output signal	5
5.5 Prevention of accidental operation	5
5.6 Prevention of defeat	5
5.7 Re-initiation of the output signal	5
5.8 Synchronous actuation	5
6 Two hand control safety functions	6
6.1 Prevention of unexpected start-up	6
6.2 Releasing of actuators	6
6.3 Synchronous actuation	6
7 Prevention of accidental actuation and of defeat	6
7.1 Common considerations	6
7.2 Prevention of defeat using one hand	7
7.3 Prevention of defeat using the hand and elbow of the same arm	7
7.4 Prevention of defeat using the forearm(s) or elbow(s)	7
7.5 Prevention of defeat using one hand and any other part of the body	7
7.6 Measures to prevent blocking of control actuating device(s)	8
7.7 Accidental actuation	8
8 General requirements	8
8.1 Ergonomic requirements	8
8.2 Operating conditions and environmental influences	8
8.3 Enclosures	9
8.4 Selection, design and installation of control actuating devices	9
8.5 Prevention of unintended output signals by acceleration forces	9
8.6 Unintended operation of hand-held machines	9
8.7 Relocatable THCDs	10
8.8 Safety distance	10
9 Verification and validation	11
9.1 General requirements for verification and validation	11
9.2 Visual inspection	12
9.3 Performance test	12
9.4 Measurement	12
9.5 Prevention of defeat	12
10 Marking	12
11 Information for installation, use and maintenance	13
11.1 Information for use	13
11.2 Installation instructions	13
11.3 Operating instructions	14
11.4 Maintenance instructions	14

Annex A (normative) Measurement test for the prevention of defeat.....	15
Bibliography	21

POLSKI KOMITET NORMALIZACYJNY 2022

1	Introduction	1
2	Scope	1
3	Normative references	1
4	Terms and definitions	1
5	THCP selection and THCP types	4
6	6.1 Selection	4
7	6.2 Types of THCP	4
8	Requirements for the design of two-hand control devices	5
9	9.1 General	5
10	9.2 Use of lockout/tagout (a synchronous action)	5
11	9.3 Prevention of accidental activation by hand and output signal(s)	5
12	9.4 Prevention of the output signal	5
13	9.5 Prevention of accidental operation	5
14	9.6 Prevention of defeat	5
15	9.7 Re-activation of the output signal	5
16	9.8 Synchronous activation	5
17	Two-hand control safety functions	6
18	18.1 Prevention of unexpected start-up	6
19	18.2 Retaining of actuators	6
20	18.3 Synchronous activation	6
21	Prevention of accidental activation and of defeat	7
22	21.1 Common considerations	7
23	21.2 Prevention of defeat using one hand	7
24	21.3 Prevention of defeat using the hand and elbow of the same side	7
25	21.4 Prevention of defeat using the forearm(s) or elbow(s)	7
26	21.5 Prevention of defeat using one hand and any other part of the body	7
27	21.6 Measures to prevent blocking of control actuating device(s)	7
28	21.7 Accidental activation	7
29	General requirements	8
30	30.1 Ergonomic requirements	8
31	30.2 Operating conditions and environmental influences	8
32	30.3 Reliability	8
33	30.4 Selection, design and installation of control actuating devices	8
34	30.5 Prevention of unintended output signals by acceleration forces	8
35	30.6 Unintended operation of hand-held actuators	8
36	30.7 Reliability of THCP	8
37	30.8 Safety distance	8
38	Verification and validation	9
39	39.1 General requirements for verification and validation	9
40	39.2 Visual inspection	9
41	39.3 Functional testing	9
42	39.4 Prevention of defeat	9
43	Marking	10
44	Information for installation, use and maintenance	11
45	45.1 Information for use	11
46	45.2 Installation instructions	11
47	45.3 Operating instructions	11
48	45.4 Maintenance instructions	11