

CONTENTS

FOREWORD.....	12
INTRODUCTION.....	14
1 General scope.....	15
1.2 Normative references.....	15
Fuse system A – D type fuse system.....	16
1 General.....	16
1.1 Scope.....	16
2 Terms and definitions.....	16
3 Conditions for operation in service.....	16
4 Classification.....	16
5 Characteristics of fuses.....	16
5.2 Rated voltage.....	16
5.3.1 Rated current of the fuse-link.....	17
5.3.2 Rated current of the fuse-holder.....	17
5.3.3 Rated current of the gauge-piece.....	17
5.5 Rated power dissipation of a fuse-link and rated acceptable power dissipation of a fuse-holder.....	17
5.6 Limits of time-current characteristics.....	17
5.6.1 Time-current characteristics, time-current zones and overload curves.....	17
5.6.2 Conventional times and currents.....	17
5.6.3 Gates.....	18
5.7 Breaking range and breaking capacity.....	18
5.7.2 Rated breaking capacity.....	18
6 Markings.....	18
6.4 Marking of the gauge-pieces.....	18
7 Standard conditions for construction.....	19
7.1 Mechanical design.....	19
7.1.2 Connections including terminals.....	19
7.1.3 Fuse-contacts.....	19
7.1.4 Construction of a gauge-piece.....	19
7.1.6 Construction of a fuse-carrier.....	20
7.1.7 Construction of a fuse-link.....	20
7.1.8 Non-interchangeability.....	20
7.1.9 Construction of a fuse-base.....	21
7.2 Insulating properties and suitability for isolation.....	21
7.3 Temperature rise, power dissipation of the fuse-link and acceptable power dissipation of the fuse-holder.....	22
7.7 I^2t characteristics.....	22
7.7.1 Pre-arcing I^2t values.....	22
7.7.2 Operating I^2t values.....	23
7.8 Overcurrent discrimination of "gG" fuse-links.....	23
7.9 Protection against electric shock.....	23
8 Tests.....	23
8.1.4 Arrangement of the fuse and dimensions.....	24
8.2 Verification of the insulating properties and the suitability for isolation.....	25

8.2.1	Arrangement of the fuse-holder	25
8.2.6	Creepage distances, clearances and distances through sealing compound.....	25
8.3	Verification of temperature rise and power dissipation	25
8.3.1	Arrangement of the fuse	25
8.3.3	Measurement of the power dissipation of the fuse-link	26
8.3.5	Acceptability of test results	26
8.5.1	Arrangement of the fuse	27
8.5.2	Characteristics of the test circuit.....	27
8.5.5	Test method	27
8.5.8	Acceptability of test results	27
8.7.4	Verification of overcurrent discrimination	27
8.9	Verification of resistance to heat	28
8.9.1	Fuse-base	28
8.9.2	Fuse-carrier	29
8.10	Verification of non-deterioration of contacts.....	30
8.10.1	Arrangement of the fuse	30
8.10.2	Test method	30
8.10.3	Acceptability of test results	31
8.11	Mechanical and miscellaneous tests.....	31
8.11.1	Mechanical strength	31
Annex AA	(informative) Special test for cable overload protection (for fuse system A).....	66
Fuse system B – Cylindrical fuses (NF cylindrical fuse system).....		67
1	General	67
1.1	Scope.....	67
2	Terms and definitions	67
3	Conditions for operation in service.....	67
4	Classification.....	68
5	Characteristics of fuses	68
5.2	Rated voltage	68
5.3.1	Rated current of the fuse-link.....	68
5.3.2	Rated current of the fuse-holder	68
5.5	Rated power dissipation of a fuse-link and rated acceptable power dissipation of a fuse-holder	68
5.6.2	Conventional times and currents.....	68
5.6.3	Gates	69
5.7.2	Rated breaking capacity	69
6	Markings	69
7	Standard conditions for construction.....	69
7.1	Mechanical design.....	69
7.1.2	Connections including terminals	69
7.1.6	Construction of a fuse-carrier	70
7.1.7	Construction of a fuse-link	70
7.1.8	Non-interchangeability	70
7.1.9	Construction of a fuse-base.....	70
7.2	Insulating properties and suitability for isolation	71

7.3	Temperature rise, power dissipation of the fuse-link and acceptable power dissipation of the fuse-holder.....	72
7.7	I^2t characteristics	72
7.7.1	Pre-arcing I^2t values.....	72
7.7.2	Operating I^2t values.....	72
7.8	Overcurrent discrimination of "gG" fuse-links.....	72
7.9	Protection against electric shock	72
8	Tests.....	73
8.1.6	Testing of fuse-holders	73
8.3.1	Arrangement of the fuse	73
8.3.3	Measurement of the power dissipation of the fuse-link.....	74
8.4	Verification of operation	75
8.4.1	Arrangement of the fuse	75
8.5	Verification of the breaking capacity	75
8.5.1	Arrangement of the fuse	75
8.5.5	Test method	76
8.5.8	Acceptability of test results.....	76
8.7.4	Verification of overcurrent discrimination	76
8.8	Verification of the degree of protection of enclosures	76
8.8.1	Verification of protection against electric shock	76
8.9	Verification of resistance to heat	76
8.10	Verification of non-deterioration of contacts.....	77
8.10.1	Arrangement of the fuse	77
8.10.2	Test method	77
8.10.3	Acceptability of test results.....	77
8.12	Verification of the reliability of terminals	81
	Fuse system C – Cylindrical fuses (BS cylindrical fuse system)	90
1	General	90
1.1	Scope.....	90
2	Terms and definitions	90
3	Conditions for operation in service.....	90
4	Classification.....	90
5	Characteristics of fuses	91
5.2	Rated Voltage	91
5.3	Rated current	91
5.3.1	Rated current of the fuse-link.....	91
5.3.2	Rated current of the fuse-holder	91
5.5	Rated power dissipation of a fuse-link and rated acceptable power dissipation of a fuse-holder	91
5.6	Limits of time-current characteristics	91
5.6.1	Time-current characteristics, time-current curves and overload curves	91
5.6.2	Conventional times and currents.....	91
5.7	Breaking range and breaking capacity	91
5.7.2	Rated breaking capacity	91
6	Markings	92
7	Standard conditions for construction.....	92

7.1	Mechanical design.....	92
7.1.2	Connections including terminals	92
7.1.6	Construction of a fuse-carrier	92
7.1.7	Construction of a fuse-link	92
7.1.8	Non-interchangeability	92
7.1.9	Construction of a fuse-base	92
7.2	Insulating properties and suitability for isolation	92
7.3	Temperature rise, power dissipation of the fuse-link and acceptable power dissipation of the fuse-holder.....	93
7.7	I^2t characteristics	93
7.9	Protection against electric shock	93
8	Tests	93
8.1	General	93
8.1.4	Arrangement of the fuse	93
8.3	Verification of temperature rise and power dissipation	93
8.3.1	Arrangement of the fuse	93
8.3.3	Measurement of the power dissipation of the fuse-link	93
8.4	Verification of operation	93
8.4.1	Arrangement of fuse	93
8.5	Verification of breaking capacity	93
8.5.1	Arrangement of the fuse	93
8.5.2	Characteristics of the test circuit.....	93
8.5.5	Test method	94
8.5.8	Acceptability of test results	94
8.10	Verification of non-deterioration of contacts	94
8.10.1	Arrangement of the fuse	94
8.10.2	Test method	94
8.10.3	Acceptability of test results	94
	Fuse system D – Cylindrical fuses (Italian cylindrical fuse system)	104
1	General	104
1.1	Scope.....	104
2	Terms and definitions	104
3	Conditions for operation in service.....	104
4	Classification	104
5	Characteristics of fuses	104
5.3.1	Rated current of the fuse-link.....	104
5.3.2	Rated current of the fuse-holder	105
5.5	Rated power dissipation of a fuse-link and rated acceptable power dissipation of a fuse-holder	105
5.6	Limits of time-current characteristics	106
5.6.1	Time-current characteristics, time-current zones and overload curves	106
5.6.2	Conventional times and currents.....	106
5.6.3	Gates	106
5.7.2	Rated breaking capacity	106
6	Markings	107
7	Standard conditions for construction.....	107
7.1	Mechanical design.....	107

7.1.2	Connections including terminals	107
7.1.6	Construction of a fuse-carrier	107
7.1.7	Construction of a fuse-link	107
7.1.8	Non-interchangeability	108
7.1.9	Construction of a fuse-base	108
7.2	Insulating properties and suitability for isolation	108
7.3	Temperature rise, power dissipation of the fuse-link and acceptable power dissipation of the fuse-holder	109
7.7	I^2t characteristics	109
7.7.1	Minimum pre-arcing I^2t values at 0,01 s	109
7.7.2	Maximum operating I^2t values at 0,01 s	110
7.9	Protection against electric shock	110
8	Tests	110
8.1.6	Testing of the fuse-holder	110
8.3	Verification of temperature rise and power dissipation	111
8.3.1	Arrangement of the fuse	111
8.3.3	Measurement of the power dissipation of the fuse-link	111
8.4	Verification of operation	112
8.4.1	Arrangement of the fuse	112
8.5	Verification of the breaking capacity	112
8.5.1	Arrangement of the fuse	112
8.5.5	Test method	112
8.5.8	Acceptability of test results	112
8.7.4	Verification of discrimination	112
8.9	Verification of resistance to heat	112
8.9.1	Test in heating cabinet	112
8.9.2	Ball-pressure test	113
8.10	Verification of non-deterioration of contacts	113
8.10.1	Arrangement of the fuse	113
8.10.2	Test method	113
8.10.3	Acceptability of test results	114
8.11	Mechanical and miscellaneous tests	114
	Fuse system E – Pin-type fuses	124
1	General	124
1.1	Scope	124
2	Terms and definitions	124
2.3	Characteristic quantities	124
3	Conditions for operation in service	125
4	Classification	125
5	Characteristics of fuses	125
5.3.3	Rated current of the gauge-piece	125
5.5	Rated power dissipation of the fuse-link	125
5.6	Limits of time-current characteristics	125
5.6.2	Conventional times and currents	125
5.6.3	Gates	125
5.7.2	Rated breaking capacity	126
6	Markings	126

6.1	Markings of fuse-holders	126
6.2	Markings of fuse-links.....	126
6.4	Markings of the gauge-pieces.....	126
7	Standard conditions for construction.....	126
7.1.4	Construction of the gauge-piece	126
7.1.6	Construction of a fuse-carrier	126
7.1.7	Construction of a fuse-link.....	127
7.1.8	Non-interchangeability	127
7.1.9	Construction of a fuse-base.....	127
7.3	Temperature rise, power dissipation of the fuse-link and acceptable power dissipation of the fuse-holder.....	127
7.9	Protection against electric shock	128
8	Tests	128
8.3	Verification of temperature rise and power dissipation	128
8.3.1	Arrangement of the fuse	128
8.3.3	Measurement of the power dissipation of the fuse-link.....	128
8.3.4	Test method	129
8.5.5	Test method	130
8.10	Verification of non-deterioration of contacts.....	130
8.10.1	Arrangement of the fuse	130
8.10.2	Test method	130
8.10.3	Acceptability of test results.....	131
	Fuse system F – Cylindrical fuse-links for use in plugs (BS plugtop system)	137
1	General	137
1.1	Scope.....	137
2	Terms and definitions	137
3	Conditions for operation in service.....	137
4	Classification.....	137
5	Characteristics of fuses	137
5.2	Rated voltage	137
5.3.1	Rated current of the fuse-link.....	138
5.3.2	Rated current of the fuse-holder	138
5.5	Rated power dissipation of a fuse-link and rated acceptable power dissipation of a fuse-holder	138
5.6.1	Time-current characteristics, time-current zones and overload curves	138
5.6.2	Conventional times and currents.....	138
5.6.3	Gates	138
5.7.2	Rated breaking capacity	138
6	Markings	138
7	Standard conditions for construction.....	139
7.1.7	Construction of a fuse-link	139
7.1.8	Non-interchangeability.....	139
7.2	Insulating properties and suitability for isolation	139
7.3	Temperature rise, power dissipation of the fuse-link and acceptable power dissipation of the fuse-holder.....	139
7.7	I^2t characteristics	139
7.7.1	Pre-arcing I^2t values.....	139

7.9	Protection against electric shock	139
8	Tests	140
8.1.4	Arrangement of the fuse-link for tests	140
8.1.5	Testing of fuse-links	140
8.2.4	Acceptability of test results	141
8.3	Verification of temperature rise and power dissipation	142
8.3.1	Arrangement of the fuse	142
8.3.4	Test method	142
8.3.5	Acceptability of test results	142
8.4	Verification of operation	142
8.4.1	Arrangement of the fuse	142
8.5	Breaking-capacity tests	143
8.5.1	Arrangement of the fuse	143
8.5.2	Characteristics of the test circuit	143
8.5.4	Calibration of the test circuit	143
8.5.5	Test method	143
8.5.8	Acceptability of test results	143
8.7	Verification of I^2t characteristics and overcurrent discrimination	144
8.7.3	Verification of compliance for fuse-links at 0,01 s	144
8.10	Verification of non-deterioration of contacts	144
8.11.1	Mechanical strength	144
Annex BB (informative) (for all fuse systems) – Alternative tests for tests No. 1 and No. 2 of Table 20 of IEC 60269-1		150
Annex CC (informative) Recommendations for future designs of fuses (for all fuse systems)		152
Bibliography		153
Figure 101 – Time-current zones for "gG" fuse-links		35
Figure 102 – Time-current zones for "gG" fuse-links		36
Figure 103 – Time-current zone for "gG" fuse-links 13 A		37
Figure 104 – Dummy fuse-links according to 8.3 and 8.9.1.1		38
Figure 105 – Test rigs for fuse-links		39
Figure 106 – Test rigs for fuse-links		40
Figure 107 – Test arrangement for fuse-bases according to 8.9.1.2		41
Figure 108 – Example of a torque wrench according to 8.9.2		42
Figure 109 – Measuring points for the voltage drop (B, C) or the temperature rise (A, D)		43
Figure 110 – Fuse-link, D-type. Sizes D01-D03		44
Figure 111 – Fuse-link, D-type. Sizes DII-DIV		45
Figure 112 – Fuse-carrier, D-type. Sizes D01-D03		47
Figure 113 – Fuse-carrier, D-type. Sizes DII-DIII		48
Figure 114 – Fuse-carrier, D-type. Size DIV		49
Figure 115 – Edison thread for D-type fuses; limit dimensions		50
Figure 116 – Gauges for Edison thread for D-type fuses for screwed shells of fuse-carrier go ring gauges		51
Figure 117 – Gauges for Edison thread, D-type fuses, go and not-go plug gauges for screwed shells of fuse-bases		52
Figure 118 – Fuse-base, D-type. Sizes D01-D03		54

Figure 119 – Fuse-base, D-type. Sizes DII-DIV	55
Figure 120 – Fuse-base, D-type for push-in gauge pieces. Size DII-DIII	57
Figure 121 – Gauge-piece and hand-key, D-type. Sizes D01-D03	59
Figure 122 – Gauge-piece and hand-key, D-type. Sizes DII-DIV	60
Figure 123 – Gauge-piece and hand-key, D-type push-in gauge rings. Size DII-DIII	62
Figure 124 – Whitworth thread W 3/16 for screw-in gauge rings and corresponding fuse-bases of sizes DII and DIII	64
Figure 125 – Gauges C 17 for concentricity of fuse-bases	65
Figure 201 – Fuse-link	82
Figure 202 – Dummy fuse-link	83
Figure 203 – Test-rig and ferrules for the measurement of the voltage drop and the verification of operating characteristics of the cartridge	84
Figure 204 – Fuse-base, A-type and B-type	86
Figure 205 – Housing for verification of operation of the fuse-links with a test rig according to Figure 203	87
Figure 206 – Test rig and ferrules for verification of breaking capacity	88
Figure 207 – Gauge for verification of the upholding of the cartridge in the fuse-carrier during withdrawal	89
Figure 301 – Details of cylindrical fuse-links	96
Figure 302 – Typical outline dimensions of carriers and bases for 230 V cylindrical fuse-links	97
Figure 303 – Typical carrier and base for 400 V cylindrical fuse-links	98
Figure 304 – Time-current zones for "gG" fuse-link	99
Figure 305 – Time-current zones for "gG" fuse-link	100
Figure 306 – Standard test rig for power-dissipation test	101
Figure 307 – Breaking-capacity test rig	102
Figure 401 – Cylindrical fuse-link type C	118
Figure 402 – Fuse-base	119
Figure 403 – Time-current zones	120
Figure 404 – Time-current zones	121
Figure 405 – Test rig	122
Figure 406 – Dummy fuse-link	123
Figure 407 – Housing for verification of operation of the fuse-links	123
Figure 501 – Pin-type fuses – Fuse-links	133
Figure 502 – Pin-type fuses – Fuse-holder	134
Figure 503 – Pin-type fuses – Gauge-pieces 230 V	135
Figure 504 – Dummy fuse-link for the temperature-rise test	136
Figure 601 – Dimensions for cylindrical fuse-links (primarily used in plugs)	145
Figure 602 – Time-current zones for "gG" fuse-links	146
Figure 603 – Test fuse-base	147
Figure 604 – Typical diagram of the circuit used for breaking-capacity tests	149
Figure BB.1 – Instant of making for Test No. 1	151
Table 101 – Maximum values of power dissipation	17
Table 102 – Conventional time and current for "gG" fuse-links	18

Table 103 – Gates for specified pre-arcing times of "gG" fuse-links with rated currents 2 A, 4 A, 6 A, 10 A, 13 A and 35 A.....	18
Table 104 – Cross-sections of rigid (solid or stranded) or flexible copper conductors.....	19
Table 105 – Creepage distances, clearances and distances through sealing compound.....	22
Table 106 – Temperature-rise limits for terminals.....	22
Table 107 – Pre-arcing I^2t values at 0,01 s for "gG" fuse-links.....	23
Table 108 – I^2t values for the discrimination with circuit breakers.....	23
Table 109 – Survey of tests on fuse-links.....	24
Table 110 – Survey of tests on fuse-bases, fuse-carriers and gauge-pieces.....	24
Table 111 – Test torque for verification of temperature rise and power dissipation.....	26
Table 112 – Test according to 8.5.5.1.....	27
Table 113 – Test currents and I^2t limits for the discrimination test.....	28
Table 114 – Power dissipation of a dummy fuse-link at rated and conventional fusing currents including tolerances.....	29
Table 115 – Test-torque for mechanical strength.....	32
Table 116 – Mechanical strength of screw-thread.....	33
Table 201 – Maximum values of rated power dissipation and values of rated acceptable power dissipation.....	68
Table 202 – Conventional times and currents for "gG" fuse-links.....	69
Table 203 – Gates for specified pre-arcing times of "gG" fuse-links with rated currents lower than 16 A.....	69
Table 204 – Minimum rated breaking capacities.....	69
Table 205 – Nominal section of copper conductors that the terminals shall accept.....	70
Table 206 – Creepage distances and clearances.....	71
Table 207 – Temperature rise limits for terminals.....	72
Table 208 – Pre-arcing I^2t values at 0,01 s for "gG" fuse-links.....	72
Table 209 – Survey of tests on fuse-link.....	73
Table 210 – Survey of tests on fuse-holder and number of fuse-holders to be tested.....	73
Table 211 – Screw-thread diameters and applied torques.....	74
Table 212 – Values concerning the choice and the adjustment of the test base.....	75
Table 213 – Values for adjustment of the test base.....	75
Table 214 – Hammer and height of fall for test for verification of resistance to shocks.....	79
Table 215 – Torque to be applied to the fuse-carrier.....	80
Table 216 – Mechanical strength of screw-thread.....	80
Table 301 – Conventional time and current for "gG" fuse-links.....	91
Table 302 – Temperature-rise limits for terminals.....	93
Table 303 – Mechanical strength of screw-thread.....	95
Table 401 – Fuse-links: rated currents, sizes and colours of indicating devices (if any).....	105
Table 402 – Rated currents of fuse-holders.....	105
Table 403 – Maximum rated power dissipation of fuse-links.....	105
Table 404 – Rated acceptable power dissipation of fuse-holder.....	106
Table 405 – Conventional times and currents for fuse-links of $I_n < 16$ A.....	106
Table 406 – Gates for specified pre-arcing times of "gG" fuse-links with rated currents lower than 16 A.....	106
Table 407 – Minimum rated breaking capacities.....	107

Table 408 – Cross-sectional areas.....	107
Table 409 – Creepage distances and clearances	109
Table 410 – Temperature-rise limits for terminals	109
Table 411 – Minimum pre-arcing I^2t values at 0,01 s	110
Table 412 – Maximum operating I^2t values at 0,01 s	110
Table 413 – Survey of the complete tests on fuse-holders and number of fuse-holders to be tested	111
Table 414 – Contact forces of the test rig	111
Table 415 – Torque to be applied to the screw-type fuse-carrier	112
Table 416 – Mechanical strength of screw-thread	114
Table 501 – Maximum values of rated power dissipation.....	125
Table 502 – Conventional times and currents for fuse-links of $I_n < 16$ A.....	125
Table 503 – Gates for specified pre-arcing times of "gG" fuse-links with rated currents lower than 16 A.....	126
Table 504 – Temperature-rise limits for terminals	128
Table 505 – Torques.....	128
Table 506 – Cross-sectional areas.....	129
Table 507 – Power dissipation of the dummy fuse-link.....	129
Table 508 – Dummy fuse-link.....	130
Table 509 – Mechanical strength of screw-thread	132
Table 601 – Conventional times and conventional currents.....	138
Table 602 – Gates for specified pre-arcing times of "gG" fuse-links for use in plugs.....	138
Table 603 – Temperature-rise limits for terminals	139
Table 604 – Pre-arcing I^2t values at 0,01 s for "gG" fuse-links	139
Table 605 – Survey of tests on fuse-links.....	141
Table 606 – Values for breaking-capacity tests.....	143
Table B.1 – Approximate values of prospective currents for breaking capacity test No. 2... 150	