

CONTENTS

FOREWORD 6

1 Scope..... 8

2 Normative references..... 8

3 Terms and definitions..... 8

 3.1 Measuring systems 9

 3.2 Components of a measuring system..... 9

 3.3 Scale factors 10

 3.4 Rated values 11

 3.5 Definitions related to dynamic behaviour 11

 3.6 Definitions related to uncertainty..... 13

 3.7 Definitions related to tests on measuring systems 14

4 Procedures for qualification and use of measuring systems..... 15

 4.1 General principles..... 15

 4.2 Schedule of performance tests 16

 4.3 Schedule of performance checks 16

 4.4 Requirements for the record of performance 16

 4.4.1 Contents of the record of performance 16

 4.4.2 Exceptions 17

 4.5 Operating conditions 17

 4.6 Uncertainty..... 17

5 Tests and test requirements for an approved measuring system and its components 18

 5.1 General requirements..... 18

 5.2 Calibration – Determination of the scale factor 19

 5.2.1 Calibration of measuring systems by comparison with a reference measuring system (preferred method) 19

 5.2.2 Determination of the scale factor of a measuring system from the scale factors of its components (alternative method)..... 22

 5.3 Linearity test..... 23

 5.3.1 Application 23

 5.3.2 Alternative methods in order of suitability 24

 5.4 Dynamic behaviour..... 25

 5.4.1 General..... 25

 5.4.2 Determination of the amplitude/frequency response..... 25

 5.4.3 Reference method for impulse voltage measuring systems 26

 5.5 Short-term stability..... 26

 5.6 Long-term stability..... 26

 5.7 Ambient temperature effect 27

 5.8 Proximity effect..... 27

 5.9 Software effect 27

 5.10 Uncertainty calculation of the scale factor..... 27

 5.10.1 General..... 27

 5.10.2 Uncertainty of the calibration..... 28

 5.10.3 Uncertainty of measurement using an approved measuring system 29

 5.11 Uncertainty calculation of time parameter measurement (impulse voltages only)..... 30

 5.11.1 General..... 30

5.11.2	Uncertainty of the time parameter calibration	30
5.11.3	Uncertainty of time parameter measurement using an approved measuring system	31
5.12	Interference test (transmission system and instrument for impulse voltage measurements)	32
5.13	Withstand tests of converting device	32
6	Measurement of direct voltage	33
6.1	Requirements for an approved measuring system.....	33
6.1.1	General.....	33
6.1.2	Uncertainty contributions	33
6.1.3	Requirement on converting device	33
6.1.4	Dynamic behaviour for measuring voltage changes.....	33
6.2	Tests on an approved measuring system	33
6.3	Performance check	34
6.3.1	General.....	34
6.3.2	Comparison with an approved measuring system	34
6.3.3	Check of the scale factors of the components	35
6.4	Measurement of ripple amplitude	35
6.4.1	Requirements	35
6.4.2	Uncertainty contributions	35
6.4.3	Calibrations and tests on an approved ripple voltage measuring system	35
6.4.4	Measurement of the scale factor at the ripple frequency.....	35
6.4.5	Dynamic behaviour by amplitude/frequency response	35
6.4.6	Performance check for ripple measuring system.....	36
7	Measurement of alternating voltage	36
7.1	Requirements for an approved measuring system.....	36
7.1.1	General.....	36
7.1.2	Uncertainty contributions	36
7.1.3	Dynamic behaviour.....	36
7.2	Tests on an approved measuring system	38
7.3	Dynamic behaviour test	38
7.4	Performance check	38
7.4.1	General.....	38
7.4.2	Comparison with an approved measuring system	38
7.4.3	Check of the scale factors of the components	39
8	Measurement of lightning impulse voltage	40
8.1	Requirements for an approved measuring system.....	40
8.1.1	General.....	40
8.1.2	Uncertainty contributions	40
8.1.3	Requirement on measuring instrument	40
8.1.4	Dynamic behaviour.....	40
8.1.5	Connection to the test object.....	40
8.2	Tests on an approved measuring system	41
8.3	Performance test on measuring systems	42
8.3.1	Reference method (preferred)	42
8.3.2	Alternative method supplemented by a measurement of the step response according to Annex C	42
8.4	Dynamic behaviour test	43

8.4.1	Comparison with a reference measuring system (preferred).....	43
8.4.2	Alternative method based on step response parameters (Annex C)	43
8.5	Performance check	43
8.5.1	Comparison with an approved measuring system	43
8.5.2	Check of the scale factors of the components	43
8.5.3	Dynamic behaviour check by reference record	43
9	Measurement of switching impulse voltage.....	43
9.1	Requirements for an approved measuring system.....	43
9.1.1	General.....	43
9.1.2	Uncertainty contribution	44
9.1.3	Requirements for the measuring instrument	44
9.1.4	Dynamic behaviour.....	44
9.1.5	Connection to the test object	44
9.2	Tests on an approved measuring system	44
9.3	Performance test on measuring systems	44
9.3.1	Reference method (preferred)	44
9.3.2	Alternative methods supplemented by a step response measurement	45
9.4	Dynamic behaviour test by comparison.....	45
9.5	Performance check	45
9.5.1	Scale factor check by comparison with an approved measuring system	45
9.5.2	Check of the scale factors of the components	45
9.5.3	Dynamic behaviour check by reference record	45
10	Reference measuring systems	47
10.1	Requirements for reference measuring systems	47
10.1.1	Direct voltage	47
10.1.2	Alternating voltage	47
10.1.3	Full and chopped lightning and switching impulse voltages.....	47
10.2	Calibration of a reference measuring system.....	47
10.2.1	General.....	47
10.2.2	Reference method: Comparative measurement	47
10.2.3	Alternative method for impulse voltages: Measurement of scale factor and evaluation of step response parameters	47
10.3	Interval between successive calibrations of reference measuring systems	47
10.4	Use of reference measuring systems.....	48
Annex A (informative)	Uncertainty of measurement	49
Annex B (informative)	Examples for the calculation of measuring uncertainties in high-voltage measurements	57
Annex C (informative)	Step response measurements	65
Annex D (informative)	Convolution method for the determination of dynamic behaviour from step response measurements.....	70
Bibliography		73
Figure 1	– Amplitude-frequency response with examples for limit frequencies (f_1 ; f_2).....	12
Figure 2	– Calibration by comparison over the full voltage range	20
Figure 3	– Uncertainty contributions of the calibration (example with minimum of 5 voltage levels).....	21
Figure 4	– Calibration by comparison over a limited voltage range, with an additional linearity test.....	22

Figure 5 – Linearity test of the measuring system with a linear device in the extended voltage range 24

Figure 6 – Shaded area for acceptable normalised amplitude-frequency responses of measuring systems intended for single fundamental frequencies f_{nom} (to be tested in the range $(1...7)f_{nom}$) 37

Figure 7 – Shaded area for acceptable normalised amplitude-frequency responses of measuring systems intended for a range of fundamental frequencies f_{nom1} to f_{nom2} (to be tested in the range f_{nom1} to $7 f_{nom2}$) 38

Figure A.1 – Normal probability distribution $p(x)$ 55

Figure A.2 – Rectangular probability distribution $p(x)$ 56

Figure B.1 – Comparison between the system under test, X, and the reference system, N ... 64

Figure B.2 – Front time deviation ΔT_{1j} of system X, related to the reference system N, and their mean ΔT_{1m} in the range of $T_1 = 0,8 \mu s \dots 1,6 \mu s$ 64

Figure C.1 – Definitions of response parameters 68

Figure C.2 – A unit-step response $g(t)$ showing an initial distortion of initial distortion time T_0 69

Figure C.3 – Suitable circuits for step response measurement 69

Table 1 – Tests required for an approved direct voltage measuring system 34

Table 2 – Required tests for uncertainty contributions in ripple measurement 36

Table 3 – Tests required for an approved alternating voltage measuring system 39

Table 4 – Tests required for an approved lightning impulse voltage measuring system 41

Table 5 – Tests required for a switching impulse voltage measuring system 46

Table 6 – Recommended response parameters for impulse voltage reference measuring systems 48

Table A.1 – Coverage factor k for effective degrees of freedom ν_{eff} ($p = 95,45 \%$) 54

Table A.2 – Schematic of an uncertainty budget 55

Table B.1 – Result of the comparison measurement at a single voltage level 58

Table B.2 – Summary of results for $h = 5$ voltage levels ($V_{Xmax} = 500 \text{ kV}$) 59

Table B.3 – Uncertainty budget of the assigned scale factor F_X 60

Table B.4 – Uncertainty budget of the assigned scale factor F 61

Table B.5 – Calibration result for front time T_1 and deviations 63

Table B.6 – Uncertainty budget of the front time deviation ΔT_{1cal} 63