

CONTENTS

FOREWORD	5
INTRODUCTION	7
1 Scope	8
2 Normative references	8
3 Terms and definitions	8
4 General test requirements	9
4.1 Accuracy of measuring instruments	9
4.1.1 Electrical measuring instruments	9
4.1.2 Temperature measurement	10
4.1.3 Electrolyte density measurement of vented lead-acid batteries	10
4.1.4 Tolerance	10
4.2 General provisions	10
4.2.1 Current slew rate	10
4.2.2 Temperature – electrolyte accessible	10
4.2.3 Temperature – electrolyte not accessible	11
4.2.4 Electrolyte density readings of vented lead-acid batteries	11
4.2.5 Mechanical support	11
4.3 Test samples	11
4.4 Test temperature	11
4.4.1 Test temperature for type testing	11
4.4.2 Operation of BMS	12
4.5 Charging and rest after charge	12
4.6 Conditioning	12
4.7 Test sequence	12
4.8 Data recording	12
4.8.1 General	12
4.8.2 Sampling frequency	12
5 Rated capacity	12
5.1 General	12
5.2 Additional test temperatures	13
6 Dynamic discharge performance test	13
6.1 Basic considerations	13
6.2 Test cycle definition without regenerative charging	13
6.3 Test cycle definition with regenerative charging	13
6.4 Definition of dynamic discharge performance	14
6.4.1 Test cycle without regenerative charging	14
6.4.2 Test cycle with regenerative charging	14
7 Dynamic endurance test	14
7.1 Basic considerations	14
7.2 Test conditions	14
7.3 Test cycle without regenerative charging	14
7.4 Test cycle with regenerative charging	14
7.5 Endurance test	14
7.5.1 Charge conditions	14
7.5.2 Rest after charge	15

7.5.3	Discharge	15
7.5.4	Cycling frequency	15
7.5.5	Capacity check	15
7.5.6	Reconditioning	15
7.5.7	End-of-life criterion	15
7.5.8	Recording	15
8	Performance testing for battery systems	15
8.1	General	15
8.2	Initial assumptions	15
8.3	Reference test cycle	16
8.3.1	Basic current discharge micro-cycle	16
8.3.2	Adjustment for vehicle performance, if required	16
8.3.3	Battery selection and preparation for test	16
8.4	General test conditions	17
8.4.1	General	17
8.4.2	Determination of battery energy content	17
8.4.3	Benchmark energy content	17
8.5	Life testing	17
8.6	Determination of maximum power and battery resistance	18
8.7	Charging tests	19
8.7.1	Charge efficiency	19
8.7.2	Partial discharge testing	19
8.7.3	Measurement of self discharge	20
8.8	Operational extremes of use	20
8.8.1	Continuous discharge at maximum vehicle system power	20
8.8.2	Recharge at maximum regenerative power as a function of state of charge	20
Annex A (normative)	Test procedures for Ni-MH batteries used for the propulsion of hybrid electric vehicles	24
Bibliography		39
Figure 1	– Test profile without regenerative charging	21
Figure 2	– Test profile with regenerative charging	21
Figure A.1	– Example of temperature measurement of cell	25
Figure A.2	– Examples of maximum dimension of cell	26
Figure A.3	– Test order of the current-voltage characteristic test (test example with batteries of rated capacity less than 20 Ah)	30
Figure A.4	– The method to obtain discharge current I_d while calculating the power density	31
Figure A.5	– Method to obtain charge current I_c while calculating regenerative power density	32
Figure A.6	– Method to obtain the internal resistance on the output side	34
Figure A.7	– Method to obtain the internal resistance on the input side	34
Figure A.8	– Current profile for HEV cycle test	36
Figure A.9	– Power profile for HEV cycle test	36
Table 1	– List of parameters for test conditions	22
Table 2	– List of charge/discharge parameters	22

Table 3 – List of DST values for one micro-cycle, where the peak power is 24 kW.....	22
Table 4 – List of DST values for one micro-cycle, adapted for a high performance vehicle.....	23
Table A.1 – Battery temperature and rest period prior to the test	24
Table A.2 – Discharge current at the battery temperature 25 °C.....	27
Table A.3 – Discharge current at the battery temperatures –20 °C, 0 °C and 45 °C	27
Table A.4 – End-of-discharge voltage	27
Table A.5 – Charge and discharge current at the battery temperatures 0 °C, 25 °C, and 45 °C	30
Table A.6 – Charge and discharge current at the battery temperature – 20 °C	30
Table A.7 – Current profile for HEV cycle test.....	37
Table A.8 – Power profile for HEV cycle test.....	38