

CONTENTS

FOREWORD.....	5
1 Scope.....	7
2 Normative references.....	7
3 Terms and definitions.....	7
4 Parameter measurement tolerances.....	9
5 Cell and battery designation and marking.....	9
5.1 Cell and battery designation.....	9
5.1.1 Small prismatic cells and cylindrical cells.....	9
5.1.2 Button cells.....	11
5.1.3 Batteries.....	11
5.2 Cell or battery termination.....	11
5.3 Marking.....	11
5.3.1 Small prismatic cells and cylindrical cells.....	11
5.3.2 Button cells.....	12
5.3.3 Batteries.....	12
5.4 Exemption of wording.....	12
6 Dimensions.....	12
6.1 Small prismatic cells and cylindrical cells.....	12
6.1.1 General.....	12
6.1.2 Small prismatic cells.....	13
6.1.3 Cylindrical cells.....	13
6.2 Button cells.....	15
7 Electrical tests.....	16
7.1 General.....	16
7.2 Charging procedure for test purposes.....	16
7.2.1 Charging procedure for cell.....	16
7.2.2 Charging procedure for battery.....	16
7.3 Discharge performance.....	17
7.3.1 General.....	17
7.3.2 Discharge performance at 20 °C.....	17
7.3.3 Discharge performance at -18 °C.....	19
7.3.4 Discharge performance for rapid charge cells (R cells).....	20
7.4 Charge (capacity) retention.....	20
7.5 Endurance.....	20
7.5.1 Endurance in cycles.....	20
7.5.2 Permanent charge endurance.....	24
7.6 Charge acceptance at constant voltage.....	28
7.7 Overcharge.....	28
7.7.1 Small prismatic cells.....	28
7.7.2 L, M, H or X cylindrical and button cells.....	29
7.7.3 LT/LU, MT/MU or HT/HU cylindrical cells.....	29
7.7.4 J cylindrical cells.....	29
7.7.5 JT cylindrical cells.....	30
7.7.6 R cylindrical cells.....	30
7.8 Safety device operation.....	31

7.9	Button cells or batteries storage, small prismatic cells or batteries storage, cylindrical cells or batteries storage	31
7.10	Charge acceptance at +55 °C for LT, MT or HT cylindrical cells	32
7.11	Trickle charge acceptance for JT cylindrical cells	32
7.12	Internal resistance	33
7.12.1	General	33
7.12.2	Measurement of the internal AC resistance	33
7.12.3	Measurement of the internal DC resistance	34
8	Mechanical tests	34
9	Safety requirements	34
10	Type approval and batch acceptance	34
10.1	General	34
10.2	Type approval	35
10.2.1	Type approval for small prismatic cells	35
10.2.2	Type approval for cylindrical and button cells	35
10.2.3	Type approval for batteries	37
10.3	Batch acceptance	38
	Bibliography	40
	Figure 1 – Jacketed cylindrical cells	13
	Figure 2 – Jacketed small prismatic cells	13
	Figure 3 – Jacketed cells dimensionally interchangeable with primary cells	14
	Figure 4 – Button cells	15
	Table 1 – Dimensions of jacketed small prismatic cells	13
	Table 2 – Dimensions of jacketed cylindrical cells dimensionally interchangeable with primary cells	14
	Table 3 – Dimensions of jacketed cylindrical cells not dimensionally interchangeable with primary cells	15
	Table 4 – Dimensions of button cells	16
	Table 5 – Discharge performance at 20 °C for small prismatic cells and cylindrical cells	17
	Table 6 – Discharge performance at 20 °C for button cells	18
	Table 7 – Discharge performance at 20 °C for batteries	18
	Table 8 – Rated capacity (mAh) compliance test (example)	19
	Table 9 – Discharge performance at –18 °C for small prismatic cells	19
	Table 10 – Discharge performance at –18 °C for cylindrical cells	19
	Table 11 – Discharge performance at –18 °C for button cells	20
	Table 12 – Endurance in cycles for small prismatic cells and cylindrical cells not dimensionally interchangeable with primary cells	21
	Table 13 – Endurance in cycles for cylindrical cells dimensionally interchangeable with primary cells	21
	Table 14 – Endurance in cycles for H or X cells	22
	Table 15 – Endurance in cycles for cylindrical X cells	22
	Table 16 – Endurance in cycles for HR or XR cells	23
	Table 17 – Endurance in cycles for button cells	23
	Table 18 – Permanent charge endurance for L, M, J, H or X cylindrical cells	24

Table 19 – Permanent charge endurance for button cells.....	24
Table 20 – Permanent charge endurance for LT, MT, or HT cylindrical cells	26
Table 21 – Permanent charge endurance for LU, MU, or HU cylindrical cells	28
Table 22 – Overcharge at 0 °C.....	29
Table 23 – Capacity deterioration due to storage period for cells or batteries.....	32
Table 24 – Charge and discharge at +55 °C.....	32
Table 25 – Trickle charge acceptance for JT cylindrical cells	33
Table 26 – Constant discharge currents used for measurement of DC resistance	34
Table 27 – Sequence of tests for type approval for small prismatic cells	35
Table 28 – Sequence of tests for type approval for cylindrical cells.....	36
Table 29 – Sequence of tests for type approval for button cells.....	37
Table 30 – Sequence of tests for type approval for batteries.....	38
Table 31 – Recommended test sequence for batch acceptance	39