

CONTENTS

FOREWORD.....	5
1 Scope.....	7
2 Normative references	7
3 Terms and definitions	7
4 Parameter measurement tolerances	9
5 Cell and battery designation and marking	10
5.1 Cell and battery designation.....	10
5.1.1 Small prismatic cells and cylindrical cells.....	10
5.1.2 Button cells.....	11
5.1.3 Batteries.....	12
5.2 Cell or battery termination.....	12
5.3 Marking.....	12
5.3.1 Small prismatic cells and cylindrical cells.....	12
5.3.2 Button cells.....	13
5.3.3 Batteries.....	13
5.4 Exemption of wording.....	13
6 Dimensions.....	13
6.1 Small prismatic cells and cylindrical cells.....	13
6.1.1 General	13
6.1.2 Small prismatic cells.....	14
6.1.3 Cylindrical cells	14
6.2 Button cells.....	16
6.3 9 V type nickel-metal hydride batteries.....	17
7 Electrical tests.....	18
7.1 General.....	18
7.2 Charging procedure for test purposes	18
7.2.1 Charging procedure for cell.....	18
7.2.2 Charging procedure for battery	18
7.3 Discharge performance	18
7.3.1 General	18
7.3.2 Discharge performance at 20 °C.....	19
7.3.3 Discharge performance at 0 °C.....	20
7.3.4 Discharge performance for rapid charge cells (R cells)	21
7.4 Charge (capacity) retention.....	21
7.5 Endurance	22
7.5.1 Endurance in cycles.....	22
7.5.2 Permanent charge endurance	25
7.6 Charge acceptance at constant voltage.....	28
7.7 Overcharge	28
7.7.1 Small prismatic, L, M, H, X, LS or MS cylindrical, and button cells.....	28
7.7.2 LT/LU, MT/MU or HT/HU cylindrical cells	29
7.7.3 J cylindrical cells	29
7.7.4 JT cylindrical cells	29
7.7.5 R cylindrical cells.....	30
7.8 Safety device operation	30
7.9 Surface temperature limitation device operation (for S cell only)	30

7.10	Storage	31
7.10.1	Button cells or batteries, small prismatic cells or batteries, cylindrical cells or batteries	31
7.10.2	Button cells or batteries, small prismatic cells or batteries, cylindrical cells or batteries (high recovery type)	32
7.11	Charge acceptance at +55 °C for LT, MT or HT cylindrical cells	33
7.12	Trickle charge acceptance for JT cylindrical cells	34
7.13	Internal resistance	34
7.13.1	General	34
7.13.2	Measurement of the internal AC resistance	35
7.13.3	Measurement of the internal DC resistance	35
8	Mechanical tests	36
9	Safety requirements	36
10	Type approval and batch acceptance	36
10.1	General	36
10.2	Type approval	36
10.2.1	Type approval for small prismatic cells and button cells	36
10.2.2	Type approval for cylindrical cells	40
10.2.3	Type approval for batteries	42
10.3	Batch acceptance	43
	Bibliography	45
	Figure 1 – Jacketed cylindrical cells	14
	Figure 2 – Jacketed small prismatic cells	14
	Figure 3 – Jacketed cells dimensionally interchangeable with primary cells	15
	Figure 4 – Button cells	17
	Figure 5 – 9 V type nickel-metal hydride batteries	17
	Table 1 – Dimensions of jacketed small prismatic cells	14
	Table 2 – Dimensions of jacketed cylindrical cells dimensionally interchangeable with primary cells	15
	Table 3 – Dimensions of jacketed cylindrical cells not dimensionally interchangeable with primary cells	16
	Table 4 – Dimensions of button cells	17
	Table 5 – Dimensions of 9 V type nickel-metal hydride batteries	18
	Table 6 – Discharge performance at 20 °C for small prismatic cells and cylindrical cells	19
	Table 7 – Discharge performance at 20 °C for button cells	19
	Table 8 – Discharge performance at 20 °C for batteries	20
	Table 9 – Rated capacity (mAh) compliance test (example)	20
	Table 10 – Discharge performance at 0 °C for small prismatic cells and cylindrical cells	21
	Table 11 – Discharge performance at 0 °C for button cells	21
	Table 12 – Endurance in cycles for small prismatic, button and cylindrical cells not dimensionally interchangeable with primary cells	22
	Table 13 – Endurance in cycles for H or X cells	23
	Table 14 – Endurance in cycles for X cells	23
	Table 15 – Endurance in cycles for HR or XR cells	24

Table 16 – Endurance in cycles for cylindrical cells dimensionally interchangeable with primary cells	24
Table 17 – Permanent charge endurance for L, M, H or X cells	25
Table 18 – Permanent charge endurance for LT, MT or HT cells	26
Table 19 – Permanent charge endurance for LU, MU or HU cells	28
Table 20 – Overcharge at 0 °C	29
Table 21 – Capacity deterioration due to storage period for cells or batteries	32
Table 22 – Capacity deterioration due to storage period for cells or batteries (high recovery type)	33
Table 23 – Charge and discharge at +55 °C	34
Table 24 – Trickle charge acceptance for JT cylindrical cells	34
Table 25 – Constant discharge currents used for measurement of DC resistance	36
Table 26 – Sequence of tests for type approval for small prismatic cells	37
Table 27 – Sequence of tests for type approval for small prismatic cells (high recovery type)	38
Table 28 – Sequence of tests for type approval for button cells	39
Table 29 – Sequence of tests for type approval for button cells (high recovery type)	40
Table 30 – Sequence of tests for type approval for cylindrical cells	41
Table 31 – Sequence of tests for type approval for cylindrical cells (high recovery type)	42
Table 32 – Sequence of tests for type approval for batteries	43
Table 33 – Sequence of tests for type approval for batteries (high recovery type)	43
Table 34 – Recommended test sequence for batch acceptance	44