

CONTENTS

FOREWORD	5
1 Scope	7
2 Normative references	7
3 Terms and definitions	7
4 Parameter measurement tolerances	10
5 General safety considerations	10
5.1 General	10
5.2 Insulation and wiring	11
5.3 Venting	11
5.4 Temperature, voltage and current management	11
5.5 Terminal contacts	11
5.6 Assembly of cells into batteries	12
5.6.1 General	12
5.6.2 Design recommendation	12
5.6.3 Mechanical protection for cells and components of batteries	13
5.7 Quality plan	13
5.8 Battery safety components	13
6 Type test and sample size	13
7 Specific requirements and tests	14
7.1 Charging procedures for test purposes	14
7.1.1 First procedure	14
7.1.2 Second procedure	14
7.2 Intended use	15
7.2.1 Continuous charging at constant voltage (cells)	15
7.2.2 Case stress at high ambient temperature (battery)	15
7.3 Reasonably foreseeable misuse	15
7.3.1 External short-circuit (cell)	15
7.3.2 External short-circuit (battery)	16
7.3.3 Free fall	16
7.3.4 Thermal abuse (cells)	16
7.3.5 Crush (cells)	17
7.3.6 Over-charging of battery	17
7.3.7 Forced discharge (cells)	17
7.3.8 Mechanical tests (batteries)	18
7.3.9 Design evaluation – Forced internal short-circuit (cells)	19
8 Information for safety	21
8.1 General	21
8.2 Small cell and battery safety information	22
9 Marking	22
9.1 Cell marking	22
9.2 Battery marking	23
9.3 Caution for ingestion of small cells and batteries	23
9.4 Other information	23
10 Packaging and transport	23
Annex A (normative) Charging and discharging range of secondary lithium ion cells for safe use	24

A.1	General.....	24
A.2	Safety of lithium ion secondary battery.....	24
A.3	Consideration on charging voltage	24
A.3.1	General	24
A.3.2	Upper limit charging voltage	24
A.4	Consideration of temperature and charging current.....	26
A.4.1	General	26
A.4.2	Recommended temperature range	26
A.4.3	High temperature range	27
A.4.4	Low temperature range	28
A.4.5	Scope of the application of charging current	29
A.4.6	Consideration of discharge	29
A.5	Sample preparation.....	30
A.5.1	General	30
A.5.2	Insertion procedure for nickel particle to generate internal short	30
A.5.3	Disassembly of charged cell	31
A.5.4	Shape of nickel particle	31
A.5.5	Insertion of nickel particle in cylindrical cell	31
A.5.6	Insertion of nickel particle in prismatic cell.....	34
A.6	Experimental procedure of the forced internal short-circuit test	36
A.6.1	Material and tools for preparation of nickel particle	36
A.6.2	Example of a nickel particle preparation procedure	37
A.6.3	Positioning (or placement) of a nickel particle	37
A.6.4	Damaged separator precaution	38
A.6.5	Caution for rewinding separator and electrode	38
A.6.6	Insulation film for preventing short-circuit	39
A.6.7	Caution when disassembling a cell	39
A.6.8	Protective equipment for safety	39
A.6.9	Caution in the case of fire during disassembling	39
A.6.10	Caution for the disassembling process and pressing the electrode core.....	39
A.6.11	Recommended specifications for the pressing device	39
Annex B (informative)	Recommendations to equipment manufacturers and battery assemblers	42
Annex C (informative)	Recommendations to the end-users	43
Annex D (normative)	Measurement of the internal AC resistance for coin cells	44
D.1	General.....	44
D.2	Method	44
Annex E (informative)	Packaging and transport.....	45
Annex F (informative)	Component standards references	46
Bibliography		47
Figure 1	– Forced discharge time chart.....	18
Figure 2	– Jig for pressing	21
Figure 3	– Ingestion gauge	22
Figure A.1	– Representation of lithium ion cells operating region for charging.....	25
Figure A.2	– Representation of lithium ion cell operating region for discharging.....	30
Figure A.3	– Shape of nickel particle.....	31

Figure A.4 – Nickel particle insertion position between positive and negative active material coated area of cylindrical cell	31
Figure A.5 – Nickel particle insertion position between positive aluminium foil and negative active material coated area of cylindrical cell	32
Figure A.6 – Disassembly of cylindrical cell	33
Figure A.7 – Nickel particle insertion position between positive and negative (active material) coated area of prismatic cell.....	34
Figure A.8 – Nickel particle insertion position between positive aluminium foil and negative (active material) coated area of prismatic cell	35
Figure A.9 – Disassembly of prismatic cells	36
Figure A.10 – Dimensions of a completed nickel particle.....	37
Figure A.11 – Positioning of the nickel particle when it cannot be placed in the specified area	38
Figure A.12 – Cylindrical cell	38
Figure A.13 – Distance / time ratio of several types of pressing devices	41
Table 1 – Sample size for type tests	14
Table 2 – Condition of charging procedure	15
Table 3 – Conditions for vibration test.....	19
Table 4 – Shock parameters	19
Table 5 – Ambient temperature for cell test.....	20
Table A.1 – Examples of operating region charging parameters	25
Table A.2 – Recommended specifications of a pressing device.....	40
Table F.1 – Component standard references	46