

NUMBERED ALLOYS

See also listings under specific types of alloys (for example, *Aluminum alloys, specific types*).

- 4-(2-pyridylazo)-resorcinol(PAR) reagent**, use in ion chromatography, **9•10**: 661.
- 5-2 1/2 alloy**. See *Titanium alloys, specific types, Ti-5Al-2.5Sn*.
- 7-14CuMo**, composition, **9•6**: 354.
- 8-8-2-3 beta alloy**. See *Titanium alloys, specific types, Ti-8Mo-8V-2Fe-3Al*.
- 8-hydroxyquinoline**
as precipitant, **9•10**: 170.
as solvent extractant, **9•10**: 170.
- 8-quinolinol**, as precipitant, **9•10**: 169.
- 10 alloy**. See *Copper alloys, specific types, C17500*.
- 13-11-3**. See *Titanium alloys, specific types, Ti-13V-11Cr-3Al*.
- 14CrMoV69 steel**, fatigue curves, **9•1**: 541.
- 14-MeV fast neutron activation analysis**, elemental concentrations in NBS fly ash determined using, **9•10**: 239.
- 16-25-6**
arc welding, **9•6**: 364.
broaching, **8•3**: 411, 412, 413.
composition, **8•3**: 406. **9•6**: 354.
forgeability, **8•5**: 119.
forging temperatures, **8•5**: 119.
grinding group, **8•3**: 427.
grinding ratio, **8•3**: 428.
machinability group, **8•3**: 406.
turning, power requirements, **8•3**: 406, 408.
- 17-14 Cu, Mo**, composition, **8•3**: 406.
- 17-22**, drilling, **8•3**: 418.
- 17-22A**, forging, blocker type, **8•5**: 20.
- 17-22 AS**, composition, **9•1**: 649.
- 17-22 AV**, composition, **9•1**: 649.
- 18Ni steels**. See *Maraging steels*.
- 19-9 DL**
annealing, **9•4**: 655.
arc welding, **9•6**: 364.
composition, **8•3**: 406. **9•4**: 651-652. **9•6**: 354.
drilling, **8•3**: 418.
flash welding, **9•6**: 557.
forgeability, **8•5**: 119.
forging temperatures, **8•5**: 119.
grinding group, **8•3**: 427.
machinability group, **8•3**: 406.
stress relieving, **9•4**: 655.
turning, tool life vs speeds, **8•3**: 408, 410.
- 19-9DX**, flash welding, **9•6**: 557.
- 19 alloy/20 alloy thermocouple**. See *Thermocouples, materials, nonstandard*.
- 20 geometry, variable**, RDF analysis, **9•10**: 396.
- 22 40 steel**, composition and heat treatment, **9•1**: 542.
- 25 alloy**. See *Copper alloys, specific types, C17200*.
- 30 CD 12 steel**, composition and heat treatment, **9•1**: 542.
- 31CrMoV9 steel**, composition and heat treatment, **9•1**: 542.
- 32 point groups**. See *Crystal classes*.
- 38-6-44**. See *Titanium alloys, specific types, Ti-3Al-8V-6Cr-4Zr-4Mo*.
- 50 alloy**. See *Copper alloys, specific types, C17600*.
- 55% Aluminum-zinc alloy coating**, **9•5**: 348-350.
- cooling, **9•5**: 349.
- corrosion resistance, **9•5**: 348.
- heat treating, **9•5**: 349-350.
- microstructure, **9•5**: 348-350.
- precleaning, **9•5**: 349.
- process, **9•5**: 348-349.
- steel sheet and wire, **9•5**: 348-350.
- 60 metal**. See *Tantalum alloys, specific types, Ta-10W*.
- 61 metal**. See *Tantalum alloys, specific types, "61" metal*.
- 63 metal**. See *Tantalum alloys, specific types, "63" metal*.
- 100-AR**, composition and mechanical properties, **9•1**: 621.
- 135M steel**. See *Nitralloy 135M*.
- 165 alloy**. See *Copper alloys, specific types, C17000*.
- 300M**
composition, **9•1**: 422.
heat treatment, **9•1**: 427.
mechanical properties, **9•1**: 427-429.
notches, effect on fatigue behavior, **9•1**: 668, 670.
processing, **9•1**: 427.
- 1100**
contour band sawing, **8•3**: 222.
machinability rating, **8•3**: 439, 440.
- 1100-H12**, machining, chips, **8•3**: 439, 440.
- 2011**
contour band sawing, **8•3**: 222.
machinability rating, **8•3**: 439, 440.
machining characteristics, **8•3**: 441.
- 2011-T3**
broaching, **8•3**: 447, 448.
drilling
drills, **8•3**: 448.
feed, **8•3**: 448, 449.
power requirements, **8•3**: 449.
speed, **8•3**: 448, 449.
machining
chips, **8•3**: 439, 440.
cutting force, **8•3**: 442, 443.
power requirements, **8•3**: 442.
multiple-operation machining, **8•3**: 456.
bar vs tubing, **8•3**: 442.
dimensional variation, **8•3**: 455.
vs 2011-T451, **8•3**: 441, 442.
vs 2017-T4, **8•3**: 441.
- 2011-T451**, multiple operation machining, vs 2011-T3, **8•3**: 441, 442.
- 2014**
contour band sawing, **8•3**: 222.
form turning, tool material, **8•3**: 330-331.
machinability rating, **8•3**: 439, 440.
- 2014-T4**, broaching, **8•3**: 69.
- 2014-T6**, turning, tool material, **8•3**: 330-331.
- 2017**
contour band sawing, **8•3**: 222.
machinability rating, **8•3**: 439, 440.
multiple-operation machining, **8•3**: 454.
thread rolling, rollability, **8•3**: 132.
- 2017-T4**
broaching, **8•3**: 447.
drilling
drills, **8•3**: 448.
power requirements, **8•3**: 448, 449.
- machining
cutting force, effect of feed, **8•3**: 439-440.
power requirements, **8•3**: 439-440.
mechanical properties, **8•3**: 439-440.
multiple-operation machining, vs 2011-T3, **8•3**: 441.
- 2017-T451**, multiple-operation machining, vs 2024-T351, **8•3**: 441.
- 2018**
contour band sawing, **8•3**: 222.
machinability rating, **8•3**: 439, 440.
- 2024**
chemical contour machining, **8•3**: 247.
contour band sawing, **8•3**: 222.
machinability rating, **8•3**: 439, 440.
multiple-operation machining, **8•3**: 454.
thread rolling, rollability, **8•3**: 132.
- 2024-T4**
boring, **8•3**: 446.
drilling
drills, **8•3**: 448.
power required, **8•3**: 448, 449.
machining, chips, **8•3**: 439, 440.
milling, **8•3**: 460, 461.
sawing, **8•3**: 461.
tapping, **8•3**: 112, 113.
cutting fluid, **8•3**: 453.
speed, **8•3**: 453.
- 2024-T351**
machining
cutting force, **8•3**: 442, 443.
power requirements, **8•3**: 442.
multiple-operation machining, **8•3**: 456.
vs 2017-T451, **8•3**: 441.
reaming and burnishing, **8•3**: 452.
- 2025**, contour band sawing, **8•3**: 222.
- 2219**, machinability rating, **8•3**: 439, 440.
- 2219-T39**, chemical contour machining, surface roughness, **8•3**: 248.
- 2618**, machinability rating, **8•3**: 439, 440.
- 3003**
contour band sawing, **8•3**: 222.
machinability rating, **8•3**: 439, 440.
planing, **8•3**: 446, 447.
- 3004**
contour band sawing, **8•3**: 222.
machinability rating, **8•3**: 439, 440.
- 3004-H32**, machining, chips, **8•3**: 439, 440.
- 4032**, contour band sawing, **8•3**: 222.
- 5005**, machinability rating, **8•3**: 439, 440.
- 5050**, machinability rating, **8•3**: 439, 440.
- 5052**
contour band sawing, **8•3**: 222.
machinability rating, **8•3**: 439, 440.
- 5052-F**, boring concave surface, **8•3**: 446.
- 5056**, machinability rating, **8•3**: 439, 440.
- 5083**, machinability rating, **8•3**: 439, 440.
- 5086**, machinability rating, **8•3**: 439, 440.
- 5154**, machinability rating, **8•3**: 439, 440.
- 5257**, machinability rating, **8•3**: 439, 440.
- 5357**, machinability rating, **8•3**: 439, 440.
- 5454**, machinability rating, **8•3**: 439, 440.
- 5456**, machinability rating, **8•3**: 439, 440.
- 5457**, machinability rating, **8•3**: 439, 440.
- 5557**, machinability rating, **8•3**: 439, 440.
- 5657**, machinability rating, **8•3**: 439, 440.
- 6053**, contour band sawing, **8•3**: 222.

- 6061**
 contour band sawing, **8•3**: 222.
 lapping, **8•3**: 464.
 machinability rating, **8•3**: 439, 440.
 multiple-operation machining, **8•3**: 454.
- 6061-T6**
 drilling in turret lathe, **8•3**: 75.
 machining, chips, **8•3**: 439, 440.
 multiple-operation machining, **8•3**: 456, 458.
 tapping
 tap life, **8•3**: 453.
 vs 6262-T9, **8•3**: 441.
- 6061-T651**, machining
 cutting force, **8•3**: 442, 443.
 power requirements, **8•3**: 442.
- 6063**
 contour band sawing, **8•3**: 222.
- machinability rating, **8•3**: 439, 440.
- 6063-T5**, tapping, **8•3**: 453.
- 6151**, contour band sawing, **8•3**: 222.
- 6262**
 machinability rating, **8•3**: 439, 440.
 multiple-operation machining, **8•3**: 454.
- 6262-T9**, tapping, vs 6061-T6, **8•3**: 441.
- 6463**, machinability rating, **8•3**: 439, 440.
- 7072**, chemical contour machining, **8•3**: 247.
- 7075**
 chemical contour machining, surface
 roughness, **8•3**: 248.
 contour band sawing, **8•3**: 222.
 machinability rating, **8•3**: 439, 440.
 milling
 effect of temper on feed, **8•3**: 457, 459.
 numerical control, **8•3**: 461.
- 7075-T6**
 boring, **8•3**: 446.
 drilling, **8•3**: 451.
 milling
 subzero quenching, **8•3**: 461, 462.
 tracer control, **8•3**: 461.
 multiple-operation machining close-tolerance,
 8•3: 455.
 sawing, blade life, **8•3**: 462, 463.
 skin milling, **8•3**: 460, 461.
 slotting, **8•3**: 457, 459.
- 7079**
 drilling, drill selection, **8•3**: 449-450.
 machinability rating, **8•3**: 439, 440.
- 7079-T6**, electrical discharge machining, **8•3**:
 231.
- 7178**, machinability rating, **8•3**: 439, 440.